

P.A. Of 1990 On 12/21 1996  
Madhuri PLS  
Chairman

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

MENOMINEE  
(County)

Located In:

Corner Code #

1. Public Land Survey

T37N R 25W

109

T R

T R

T R

2. Property Controlling  
in Section

S T R

S T R

3. Miscellaneous  
Property in Sec.

S T R

S T R

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_

5. Private Claims \_\_\_\_\_

I, William Lenca, in a field survey on Sep. 17, 1996, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

1852: Original Survey by George Adair - B.T.'s - Hemlock, 11" - N31°E - 25 lks.; Birch, 14" - S48°W - 28 lks. Original corner evidence was destroyed by county road improvements.

1969: L.C.R.C. No. 697 (Volume 3) recorded by Frank J. Bray, DNR Surveyor, states: "This corner was placed in road junction of north - south and west blacktopped road. Location checks well with corners in area." Set 1/2" x 12" re-rod - B.T.'s: 9" S. Maple (NBT) - N74°E - 93 links; 9" Y. Birch - (NBT) - S64°E - 98 links.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

We recovered a 1/2 inch diameter iron rod in the centerline of County Roads North - South and West, fitting the B.T.'s as shown in L.C.R.C. No. 697 (Volume 3) described in part "A". This corner has been accepted and used by local surveyors for at least 27 years, and is accepted as the best available evidence of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:  
Set 5/8" x 24" Iron Rod/3-1/4" dia. Alum. cap stamped for corner location in Monument Box:

20" dia. Beech

8" dia. Maple

5/8" x 24" Iron Rod/2" dia. Alum. cap marked "WITNESS MARKER"

4" dia. Elm

Metal Survey Sign Post

N60°E 77.54 feet

S41°E 82.98 feet

S49°W 49.80 feet

N42°W 51.69 feet

East 33.2 feet

Scr. NBT

Scr. NBT

1' NE of Tel. Box

Scr. NBT

NOTE: All bearings are magnetic bearings. All distances are measured with steel tape. Distances to trees are to nail in side of tree.

Signed by William Lenca  
Surveyor's Michigan License No. 26461

Date Dec. 26, 1996

