

FOR CORNERS OF--	LOCATED IN--	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY_____ T. _____ N. _____ E. _____ S., R. _____ W. _____		
2. PROPERTY CONTROLL- 18, T. 37N N. 27W E. ING IN SECTION _____ S., R. _____ W. _____		16, 14, 10, 7.
3. MISCELLANEOUS PROPERTY IN SECTION _____ T. _____ N. _____ E. _____ S., R. _____ W. _____		
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

MENOMINEE CO

REGISTER OF DEEDS STAMP AND
FILING NUMBER

David Babbitt

I, _____, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on January 4, 1985, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

- | | |
|---|----------------|
| 16) East 1/16 corner on the south section line of Section 18. | Not prev. est. |
| 14) South 1/16 corner on the east section line of Section 18. | " " " |
| 10) South 1/16 corner on the west section line of Section 18. | Not prev. est. |
| 7) North 1/16 corner on the east section line of Section 18. | Not prev. est. |

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

- | |
|--|
| 16) Set MPOL between the south 1/4 corner and the SE section corner of Section 18. |
| 14) Set MPOL between the east 1/4 corner and the SE section corner of Section 18. |
| 10) Set MPOL between the west 1/4 corner and the SW section corner of Section 18. |
| 7) Set MPOL between the east 1/4 corner and the NE section corner of Section 18. |

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

- | | | |
|----------------------------|----------------------------|------------------------|
| 16) DNR Monument | 14) DNR Monument | 10) DNR Mon. Monument |
| 8" Sugar Maple N37°W 36.5' | 10" W. Ash S35°W 46.6' | 4" H.Maple S64°W 15.3' |
| 6" Sugar Maple N78°E 20.9' | 8" Sugar Maple N78°W 9.4' | 5" H.Maple S03°W 26.5' |
| 5" Sugar Maple S1°E 24.45' | 6" Sugar Maple N20°E 25.4' | 5" H.Maple S62°E 20.5' |
| 6" Sugar Maple S60°W 28.7' | 9" Sugar Maple S54°E 10.3' | 5" W.Birch N26°E 16.8' |
| 7) DNR Monument | | |
| 4" B.Cherry N35°E 13.45' | | |
| 4" B.Cherry S2°W 41.9' | | |
| 12" Oak S64°W 45.4' | | |
| 14" Oak N21°W 54.9' | | |

SIGNED BY

David B. Babbitt

DATE

1-16-85

SURVEYOR'S MICHIGAN REGISTRATION NO.

21558

(SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY

DATE