

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

for corners in

Menominee (County)	Located In:	Corner Code #
1. Public Land Survey	T _____ R _____	_____
	T _____ R _____	_____
	T _____ R _____	_____
2. Property Controlling Section	S 17 T 37N R 27W	REF 64 S of E5
	S 17 T 37N R 27W	REF 64 S of 2
	S _____ T _____ R _____	_____
3. Miscellaneous Property in Sec.	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_  
5. Private Claims \_\_\_\_\_

12/19/2012AD  
Jeremy J. Pipp, in a field survey on 12/19/2012AD do hereby state  
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2  
above were in conformance with regulations and rules therefore as required in the current manual of survey  
instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of  
a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with  
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,  
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded  
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(N-N 1/64) North North One-sixty-fourth corner on the East line of Section 17.

(C-N-NE 1/64) Center North Northeast One-sixty-fourth corner of Section 17.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(N-N 1/64) Corner position established mid-point and on-line between the North One-Sixteenth corner on the East line and the Northeast corner of Section 17.

(C-N-NE 1/64) Corner position established mid-point and on-line between the Northeast One-Sixteenth corner and the East One-Sixteenth corner on the North line of Section 17.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(N-N 1/64) DNR monument  
7" Balsam N81E 11.42' (1/64S,BT)  
9" Balsam S33E 46.89' (1/64S,BT)  
5" Balsam S81W 25.51' (1/64S,BT)  
5" Ironwood N43W 50.11' (1/64S,BT)

All trees are blazed, scribed, and  
painted. Measurements are to nail in  
side of tree, bearings are magnetic.

Signed by \_\_\_\_\_  
Surveyor's Michigan License No. 50447

For the Michigan Department of Natural Resources

(C-N NE 1/64) DNR monument  
11" Maple N61E 26.00' (1/64S,BT)  
10" Maple S50E 22.00' (1/64S,BT)  
5" Maple S68W 59.12' (1/64S,BT)  
12" ASH N62W 13.66' (1/64S,BT)

All trees are blazed, scribed, and  
painted. Measurements are to nail in  
side of tree, bearings are magnetic.

Date July 18, 2013

