

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Menominee Located In: Corner Code #
Public Land Survey
Property Controlling Section
Miscellaneous Property in Sec.

Lot No. Recorded Plat
Private Claims

Jeremy J. Pipp, in a field survey on 3/12/2014
3/06/2014 do hereby state
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2
above were in conformance with regulations and rules therefore as required in the current manual of survey
instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of
Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded
on this certificate.

1. Description of original monument and accessories and/or subsequent restoration:

(03) North One-Sixteenth corner common to Sections 29 and 30. Not set in original survey. 1971:
Michigan DNR (Frank Bray PS#13575) Set 1" pipe with 4" Aluminum cap witnessed by 7" Cedar N05E
3.7', 6" Cedar S56W 8.6'.

(04) Northwest One-Sixteenth corner of Section 29. Not set in original survey, no evidence of
subsequent establishment.

3. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(03) Accepted found MDNR Monument and Two existing NBT's as a careful and faithful PERPETUATION of
the position of the original corner.

(04) Corner position established at the intersection of the North and West One-Sixteenth lines of
Section 29.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(03) DNR monument
9" Cedar S83E 16.53' (1/16S,NBT)
9" Cedar S55E 5.63' (1/16S,NBT)
EX 8" Cedar S62W 9.25' (1/16S,BT)
EX 9" Cedar N12W 1.22' (1/16S,BT)
All trees are blazed, scribed, and
painted. Measurements are to nail in
side of tree, bearings are magnetic.
(04) DNR monument
7" Tamarack N39E 16.64' (1/16S,BT)
4" Tamarack S40E 6.37' (1/16S,BT)
6" Tamarack S59W 10.59' (1/16S,BT)
4" Tamarack N46W 12.71' (1/16S,BT)
All trees are blazed, scribed, and
painted. Measurements are to nail in
side of tree, bearings are magnetic.

Signed by Surveyor's Michigan License No. 50447 Date July 9, 2014

Table with 13 rows and 13 columns (A-M) for Register of Deeds Stamp & File Number. Contains numerical data for each cell.