

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in
MISSISSAUGEE
(County)

Located In:

Corner Code ##

1. Public Land Survey T 21N R 5W J-4
T R
T R
T R
2. Property Controlling S 11 T R 3
in Section S T R
3. Miscellaneous S 11 T R +1544'-6 OF
Property in Sec. S T R COR CODE 2

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat
5. Private Claims

I, CARL F. ROSER, in a field survey on OCTOBER 22, 19 87, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

J-4

J-4 CONT.

3

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

J-4

J-4 CONT.

3

FD STK SHADOW ON S SIDE OF OLD
DDL BIT AXE HEAD (VERTICAL), 1
FT DEEP; IN APPROX CTR OF OLD
E-W DIRT RD GRADE; ACCEPTED
FOR CTR OF S-11. PROBABLY A
RESULT OF 1907 SUR & SEC SUB'N
OF S-11 BY CO SUR J.D. MCBAIN.
FD CTR OF S-11 IS WITHIN 3'
FOR LAT & 11' FOR DEP OF CALC
ST LINE INTERSEC OF 1/4 LINES.
FD 19" W(?) PINE STP W/OLD
AXE NOTCH, N40°W, 55.1; &

DROVE 5/8" X 34" REROD FOR SW
COR OF NW 1/4-NW 1/4 OF S-11.
COR FALLS IN CUT OVER AREA,
THE N EDGE OF THE WOODS LINE
BEING 50'±S.

DROVE 5/8" X 34" REROD FOR
MEANDER COR ON LINE BETN GOVT
LOT 2 & GOVT LOT 4 (E 1/8 LINE
IN NE 1/4 S-11) & JUST N OF
MUSKEGON RY. COR IS
S60°12'54"E, 1544.44' FROM
E 1/8 COR ON N LINE S-11.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

J-4

J-4 CONT.

3

DROVE 5/8" X 34" REROD W/RLS
CAP IN SHADOW OF STAKE ON S
SIDE OF FD AXE HEAD.
12" W OAK N55°W 23.6'
3" R OAK N40°E 27.0'
16" W PINE S80°E 41.1'
14" R OAK S30°W 24.1'

DROVE 5/8" X 34" REROD W/RLS
CAP & SET CED POST W/LOC TAG.
23" MAPLE S26°E 71.9
8" TM MAPLE S20°W 51.8
22" OAK W/
FORK S70°W 107.4
CTR N-S
TRL RD WEST 36'±

DROVE 5/8" X 34" REROD W/RLS
CAP & SET CED POST.
26" MAPLE N25°W 30.8'
29" MAPLE N75°W 17.9'
8" MAPLE S55°W 37.6'
NW'LY EDGE RVR DUE B 45'±
NW'LY EDGE RVR DUE E 12'±

Signed by Carl F. Roser 10-25-88 Date

Surveyor's Michigan License No. 12028

FORM APPROVED BY MICHIGAN STATE BOARD OF SURVEYORS

