

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in  
MISSAUKIEE

(County)

Located in:

Corner Code ##

1. Public Land Survey

T 21N R 6W

K-12

T R

T R

T R

2. Property Controlling  
in Section

S 26 T R

16

S 35 T R

6.7

3. Miscellaneous  
Property in Sec.

S T R

S T R

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat

5. Private Claims

I, CARL F. ROSER, in a field survey on JUNE 17, 19 91,  
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned  
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the  
current manual of survey instructions of the United States Department of the Interior, Bureau of Land  
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5  
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a  
Court of Law; established, re-established, monumented, re-monumented, recovered, found as  
expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded  
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

K-12

S-35, 6

S-26, 16

S-35, 7

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

K-12

S-35, 6

S-26, 16

S-35, 7

REESTAB'D E 1/4 COR SEC 35  
MIDWAY & ON LINE BETW SEC  
COR'S 1/2 MILE N & S. TIE TO  
N EDGE OF SWP TO S FITS US  
(BLD) TIE OF 330'. E-W WIRE  
ON STEEL FN POSTS IS 9.5'  
SOUTH. N-S SMOOTH WIRE ON  
TREES IS 86' ± EAST.

ESTABLISHED SW COR OF NE 1/4  
OF NE 1/4 OF SEC 35 PER STD  
BLM INSTRUCTIONS. CTR OF  
TRAIL RD NE - SW IS 104' NORTH  
& 66' WEST. ROW OF CEDAR  
POSTS TO EAST (150' - 200'  
APART) ARE 66' SOUTH.

ESTABLISHED THE SW COR OF  
SE 1/4 OF SE 1/4 OF SEC 26 PER  
STANDARD BLM INSTRUCTIONS.  
CTR E-W SAND ROAD IS 6 104' ±.

ESTABLISHED SE COR OF NE 1/4  
OF NE 1/4 OF SEC 35 PER STD  
BLM INSTRUCTIONS. CTR OF N-S  
TRAIL IS 141' EAST. ROW OF  
E-W STEEL FN POSTS (NO WIRE)  
IS 10' SOUTH.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-12

S-35, 6

S-26, 16

S-35, 7

SET DNR MON & CED POST.  
3" W PINE N07°E 14.6'  
17" R PINE N85°E 18.1'  
13" R PINE S15°E 54.5'  
4" W PINE S85°W 16.8'  
RANDOM LINE FROM  
NORTH WEST 2' ±

DROVE 5/8" X 34" REROD W/RLS  
CAP; SET CED POST W/LOC TAG.  
3" MAPLE N05°W 24.5'  
12" W PINE S80°E 49.2'  
4" BALSAM S85°W 48.8'

DROVE 5/8" X 34" REROD W/RLS  
CAP; SET CED POST W/LOC TAG.  
11" TW MAPLE N33°W 29.41'  
3" W PINE N80°E 21.17'  
9" MAPLE CLP S05°W 52.67'  
NE COR CABIN S75°W 42.5'

DROVE 5/8" X 34" REROD W/RLS  
CAP. SET CED POST W/LOC TAG.  
11" B CHERRY  
(CLP 4) NORTH 41.9'  
3" TW SPRUCE S50°E 34.6'  
4" W PINE S40°W 44.9'  
5" W PINE S70°W 43.9'

Signed by Carl F. Roser 12-02-92 12028

Date

Surveyor's Michigan License No.

