

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Missaukee
(County)

Located In:

Corner Code #

1. Public Land Survey

T R
T R

2. Property Controlling
in Section

T R
S 24 T 23N R 5W
S 24 T 23N R 5W

1

4

3. Miscellaneous
Property in Sec.

S T R
S T R

Register of Deeds Stamp & File Num

4. Lot No. , Recorded Plat

5. Private Claims

I, Craig W. McVean, in a field survey on March 19 97
do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the
corner points mentioned in lines 1 and 2 above were in conformance with regulations
and rules therefore as required in the current manual of survey instructions of the
United States Department of the Interior, Bureau of Land Management or by a
decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5
above were in conformance with the rules of the Michigan Board of Land Surveyors
or by a Decree of a Court of Law; established, re-established, monumented,
recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this
certificate.

A. Description of original monument and accessories and/or subsequent restoration:

1 - None.

4 - None.

| | A | B | C | D | E | F | G | H | I | J | K | L | M |
|----|---|----|---|----|---|----|---|----|---|----|---|----|---|
| 1 | | | | | | | | | | | | | |
| 2 | | 6 | | 5 | | 4 | | 3 | | 2 | | 1 | |
| 3 | | | | | | | | | | | | | |
| 4 | | 7 | | 8 | | 9 | | 10 | | 11 | | 12 | |
| 5 | | | | | | | | | | | | | |
| 6 | | 18 | | 17 | | 16 | | 15 | | 14 | | 13 | |
| 7 | | | | | | | | | | | | | |
| 8 | | 19 | | 20 | | 21 | | 22 | | 23 | | 24 | |
| 9 | | | | | | | | | | | | | |
| 10 | | 30 | | 29 | | 28 | | 27 | | 26 | | 25 | |
| 11 | | | | | | | | | | | | | |
| 12 | | 31 | | 32 | | 33 | | 34 | | 35 | | 36 | |
| 13 | | | | | | | | | | | | | |



B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

1 - W 1/16 Corner Sec. 13 & 24 - Set 2" A. C. on
5/8" x 34" Rebar per Standard BLM
Procedure. CL. of Burns Rd. is 5'N.
Single Strand Wire to S. is 13' ± W.

4 - NW 1/16 Corner Sec. 24 - Set 2" A.C.
on 5/8" x 34" Rebar per Standard
BLM Procedure.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

1 - 2" A.C. on 5/8" x 34" Rebar
South 33.01 to 2" A.C. on 5/8" x 34" Rebar
with Carsonite Post Guard on W 1/16 Line
S21°W 33.62' to N&T in W. Side 6" J. Pine
S66°W 91.33' to N&T in NW Side 8" J. Pine
N80°E 105.95' to Pk & Tag in Top N. End 15" CMP

4 - 2" A.C. on 5/8" x 34" Rebar
Set Carsonite Post 1' SW
S32°E 66.35' to N&T in N. Side 11" R. Pine
S40°W 59.14' to N&T in SE Side 12" R. Pine
East 113.45' to N&T in S. Side 11" R. Pine
N21°W 52.11' to N&T in SW Side 11" R. Pine

Signed by Craig W. McVean
Surveyor's Michigan License No. 39088

Date 3/6/1998