

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in
MISSAUKIEE

(County)

Located In:

Corner Code #

1. Public Land Survey

T 23N R 7W

1-6

T R

T R

T R

2. Property Controlling
in Section

S 14

T R

4

S 15

T R

7, 14

3. Miscellaneous
Property in Sec.

S

T R

S

T R

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat

5. Private Claims

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

I, CARL KIISKILA, in a field survey on MARCH 29, 19 95, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

1-6

4

7

(NO EVIDENCE OF G.L.O. CORNER, B.T.'S, LINE TREES & TOPOGRAPHY, AS CALLED OUT IN THE G.L.O. LINE NOTES; UNLESS NOTED IN ITEM "B" BELOW.)



B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

1-6

4

7

14

FOUND AND ACCEPTED 1/2" IRON FOR E 1/4 COR OF SEC 15 AS SET BY J. WILCOX IN 1981. SET DNR MON OVER 1/2" IRON. CTR N-S TRAIL RD IS 8' WEST. OLD N-S B/WIRE FM REMAINS ARE 17' E. TRAIL RD EAST IS 25' SOUTH & OLD E-W RR GRADE IS 390' SOUTH.

ESTABLISHED THE NW COR OF THE SE 1/4 OF THE NW 1/4 OF SEC 14; PER STD BLM INSTRUCTIONS.

ESTABLISHED THE SE COR OF THE NE 1/4 OF THE NE 1/4 OF SEC 15; PER STD BLM INSTRUCTIONS. CTR OF N-S TRAIL IS 6' W. CTR OF TRAIL ELY IS 22' S.

ESTABLISHED THE NE COR OF THE SE 1/4 OF THE SE 1/4 OF SEC 15; PER STD BLM INSTRUCTIONS. CTR OLD N-S CORDUROY RD. BED IS 3' E.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

1-6

4

7

14

SET DNR MON OVER WILCOX CAP IRON.

110" CEDAR N68°W 18.10'
15" MAPLE N01°W 9.06'
16" W. BIRCH N55°E 10.25'
15" MAPLE S31°E 4.00'
4" MAPLE N85°E 11.00'

1 WILCOX WITNESSES - NEW NAILS.

SET 5/8" X 32" CAPPED REROD & CARSONITE POST.

5" MAPLE N19°E 14.04'
4" MAPLE S74°E 8.20'
6" MAPLE S02°E 18.13'
6" OAK S54°W 17.58'

SET 5/8" X 34" REROD W/PS CAP. SET CARSONITE POST N75°W 16'.

27" W. PINE WEST 15.84'
19" W. PINE N15°W 64.46'
10" CEDAR N75°E 48.90'
14" W. PINE S30°E 55.37'

SET 5/8" X 34" REROD W/PS CAP & SET CARSONITE POST W/LOC TAG.

7" MAPLE N65°W 2.74'
4" BALSAM N75°E 9.35'
7" CEDAR S65°E 41.38'
14" CEDAR S20°W 38.00'

Signed by

Carl T. Kiiskila

Date

3-28-97

Surveyor's Michigan License No.

33981