

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in
MISSAUKEE

(County)

Located In:

Corner Code #

1. Public Land Survey

T 23N R 7W

1-2, 1-3, J-3

T R

T R

T R

2. Property Controlling
in Section

S 3 T R

14

3. Miscellaneous
Property in Sec.

S T R

4. Lot No. , Recorded Plat

5. Private Claims

Register of Deeds Stamp & File Number

I, CARL KIISKILA, in a field survey on JUNE 8, 19 95,
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the
current manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
Court of Law; established, re-established, monumented, re-monumented, recovered, found as
expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

1-2

1-3

J-3

(NO EVIDENCE OF G.L.O. CORNER, B.T.'S, LINE TREES & TOPOGRAPHY,
AS CALLED OUT IN THE G.L.O. LINE NOTES; UNLESS NOTED IN ITEM "B"
BELOW.)

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

14



B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

1-2

1-3

J-3

14

RESET THE E1/4 COR OF SEC. 3
PER J.WILCOX WIT'S (FD
1-R.PINE SW & 1-MAPLE STP NE)
AND PRORATED J.W. MEAS. ON
EAST LINE OF SEC 3, J.W. FD A
PLOW SHEAR AT THIS POSITION IN
1979, SEE L.C.R.C. PAGE 573.
COR IS IN CTR N-S PAVED RD AND
3' N OF CTR GRAVEL RD TO WEST.

FOUND 1/2" REROD FOR THE SW
COR. OF S-2 AS SET BY PS, FRED
THOMSON IN 1979. FITS L.C.R.C.
PAGE 573 WITNESSES AND
CERTIFICATE OF SURVEY LI. S-1,
PG. 526.

FOUND 1" PIPE FOR S1/4 OF S-2.
PIPE FITS FRED THOMSONS 1979
L.C.R.C., PG. 573, WITNESSES
AND HIS CERT. OF SURVEY IN
LI.S-1, PG. 526.
PIPE IS 2' SOUTH OF CTR. E-W
B.TOP ROAD.

ESTABLISHED THE SE COR OF THE
NE1/4 OF THE SE1/4 OF S-3 PER
STANDARD BLM INSTRUCTIONS.
CORNER FALLS IN CTR OF N-S
B.TOP ROAD AND ON N. EDGE OF
DRIVE TO WEST.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

1-2

1-3

J-3

14

SET 5/8" X 12" REROD W/CAP.
16" R. PINE S60°W 65.27'
10" MAPLE S60°E 57.24'
8" MAPLE N66°E 60.75'
STREETS NAME SIGN
N69°W 51.8'

FD 1/2" REROD IN CTR OF ROAD
INTERSECTION, B.TOP N-S-E-W.
12" OAK (PK) S18°E 81.76'
8" SCOTCH PINE (PK)
S31°W 94.26'
TELE POLE, PHONE RISER
SUPPORT N33°W 58.58'
POWER POLE N38°E 82.54'

FD 1" IRON PIPE IN ROAD
INTERSECTION, BLK TOP ROADS
E-W & N.
5" MAPLE S06°W 71.5'
ROAD SIGN N52°E 62.20'
TELE POLE RISER SUPPORT
N40°W 57.30'
POWER POLE S30°E 110.70'
OLD WIT BY F.H.THOMSON RLS
#21996, LIBER 5-1 PAGE 526.

SET 5/8" X 32" REROD W/CAP.
42" MAPLE S20°E 86.94'
5"x 6" PHONE RISER
POST N70°E 34.42'
8" TW MAPLE S36°W 82.90'
12" R. PINE N43°W 43.26'

Signed by

Carl T. Kiiskila

Date

3-28-97

Surveyor's Michigan License No.

33981