Land Corner Recordation Certificate Authority: 1970 PA 74, MCL 54.205

Surveyor's Name: Craig W. McVean				Field Survey Date: June 13, 2017							
For corner(s) in:	r(s) in: Missaukee		County								
Original Public	Land Survey	Corner Code									
S	Т	R									
S	Т	R			A B (CDI	EFC	ЭН	IJ	K L I	м
S	Т	R			- 1			1			j 1
S	Т	R			2 6	5	4	- 3	2		2
Property Controlling Corner				Corner Code	3	1000 000 000 000 000 0000 0000		· · · · · ·		1	3
S	T	R			4 7	8	9	10		12	4
s		R			- 5	- <u>E</u>	-!	1	1 -		5
s	T	R			6 18	- 17 -	16	15	- 14 -	13	6
S	т	R			7				· · · · · · ·	* ******	7
			-		8 19	20	21	22	23	24	8
Property Corner				Corner Code	9				9	-	9
S 23	з Т	23N R	7W	5	10 30	29	28	27	26	25	10
S	Т	R			- 11			'	20	20	
S	Т	R									11
S	т	R		-	12 31	32	- 33	- 34	- 35	-36	12
					13 <mark>AB(</mark>	DD	EFO	ΒĤ	IJ	K L M	J 13 M
Protracted Public Land Survey Corner				Corner Code							
S2	3 Т	R	7W	J8							
S	ТТ	R			2						
S	Т	R			_						
S	Т	R			_						
					-						

Part A: Corner History

<u>J8</u> – C ¼ Corner Sec. 23, T23N, R7W - None

5 – CN 1/16 Corner Sec. 23, T23N, R7W - None

Page 1 of 2

Part B: Surveyor's Report on Perpetuation, Restoration, Reestablishment, or Monumentation of Corner

- <u>J8</u> C ¼ Corner Section 23, T23N, R7W Set stamped 2" Alum. Cap on 5/8" x 34" long iron rebar at intersection of ¼ lines per Standard BLM procedure. Corner in Cedar swamp. South edge of swamp is 173'± South.
- 5 CN 1/16 Corner Sec. 23, T23N, R7W Set 2" Alum. Cap on 5/8" x 4' long iron rebar per Standard BLM procedure. Corner in saw grass and tag alder marsh. South edge of Stream – Course E'ly is 90' North.

Part C: Field Evidence of Perpetuation or Monumentation of Corner

- <u>J8</u> C ¼ corner Section 23, T23N, R7W Stamped 2" Aluminum Cap on 5/8" x 34" long iron rebar.
 Set Blue Composite Post with Loc. Tag 1' East.
 N85°W 29.51' to set N & T in SW side 16" Cedar N77°E 9.78' to set N & T in SE side 12" Cedar
 - scribed 'XBT' S29°E 22.56' to set N & T in SW side 2" W. Pine S51°W 25.48' to set N & T in NW side Twin
 - 8" & 10" R. Maple
- <u>5</u> CN 1/16 Corner Sec. 23, T23N, R7W Stamped 2" Aluminum Cap on 5/8" x 4' long iron rebar.
 Set Blue Composite Post with Loc. Tag 1' East. S45°W 34.62' to set N & T in NW side 4" Cherry S36°E 55.26' to set N & T in SW side 6" Fir N6°E 26.04' to set ½" x 18" rebar S71°E 23.89' to set ½" x 18" rebar



11/21/2017

Professional Surveyor's License No.:

Craig W. McVean

39088

Prepared By: Craig W. McVean Michigan Dept. of Natural Resources 8015 Mackinaw Trail Cadillac, Michigan 49601