LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in MISSAUKEE	ring nequireme	ent of Act 74, Mich. P.A. 1970	•	
(County)	Located In:	Corner Code ≠#		•
1. Public Land Survey	T 24N R 5N	B-6, C-6		
l ,	T R	C-7		
2. Property Controlling	S 17 T R			
in Section	S T R	10		
3. Miscellaneous	S T R	Regi	ster of Deeds Stamp &	Ella Alvanta -
Property in Sec.	S T R		- Or Deeds Stamp a	riie Number
I. Lot No, Re	corded Plat			
5. Private Claims			A B C D E F G	<u> </u>
			3	3
CARL F. ROSER	in a field average AllPhPT 4		┩╌ ┞╾ ╏	10
in iididah caitiik tiist Audet Lediti	in a field survey onAUGUST 4, rements of P.A. 74, Michigan P.A. of 197	O the corresponding to the cor	5	┞╏┩╌╏
current manual of survey instruct	onformance with regulations and rule ions of the United States Department	es therefore as required in the		1 5 14
AMERICAN CONTRACTOR OF CONTRACTOR	ourt of Law and/or that the corner point he rules of the Michigan Board of Land	de montioned in lines 2.4 s = 4.5	8 19 20 21	
ourl of Law; established, re- expressed below:	established, monumented, re-monumented	nented, recovered, found as		
API COOCU OCIUW.			10 - 30 29 28 2	262
on this certificate.	ners, all in the same town and rar		11	┊┡┋
Description of addition	m.,		13 32 33 3	1 35 36
. Description of original mo	nument and accessories and/or s	ubsequent restoration: C-7		-
NO EVIDENCE OF G.L.O. CORNER	, B.T'S, LINE TREES & TOPOGRAPHY.		10	
15 CALLED OUT IN THE 6.L.O. L	INE NOTES; UNLESS NOTED IN ITEM *8		•	
		("B" CONT.) SOUTH. LAST SPRING THERE WAS AN		•
		ACCUMULATION OF BEAR SCAT AT W		
		END OF ISLAND. E END OF ISLAND	•	
		COMING BACK TO BALSAM UNDERGROWTH. COR FALLS ON E-W		,
Description of corner avid	prop found and (an area to a second	DAME. GAME MORTH TO BUT THE		•
B-9	ence found and/or method applied C-6			•
STABLISHED CTR OF SEC 18 AT	REESTABLISHED 1/4 COR COMMON	C-7 Restored se cor of S-18 on	10 ESTABLISHED S 1/8 COR	UN N
NTERSEC OF 1/4 LINES. OLD -W NOVEN NIRE FENCE IS	TO SECTIONS 17 & 18 MID WAY &	SMALL ISLAND OF HIGHER GROUND	LINE S-17 PER STANDARD	BLM
OUTH 19' ± 1'. ALSO SEE CERT.	ON LINE BETWEEN NE & SE Corners of S-18. Found old	SURROUNDED BY BIG SWP. ISLAND HAS BALSAM, RED MAPLE, ASPEN.	INSTRUCTIONS, 'FN COR	(FN N 4
F SUR. BY L.S, NORM PARKER;	FENCE CORNER ON GROUND (MITH	W BIRCH, B CHERRY, ETC.	W) IS S25°E, 41° ±.	
IBER S-1, PG. 197. NORM How's dist from N1/4 cor S-18	FENCE REMAINS W & S) S6°E, 52'. DROVE 5/8" X 34"	RESTORED COR PER RECORD GLD		
DUTH ALONG N-S 1/4 LINE	REROD FOR POINT ON SECTION	SWP TIES E-W-N. (NO OTHER POSITION WOULD FIT SWP TIES.)		
584.5' TO EXIST. E-W FENCE	LINE S3°21'W, 397.5'.	GLO = ENT. SWP IS 2.9 CHS		
NOTHING SET OR ESTABLISHED OR ACTUAL CENTER OF SEC 18).		MEST, 0.5 CHS EAST AND 2 CHS	***	
ERT SUR WAS RECORDED 12-26-74	•	NORTH. COR FALLS AT OR NEAR ENT SWP LOOKING (CONT. IN "A")		
Description of monument to	or corner and accessories establis		ocition of the corner	
B-6	C-6			
OVE 5/8" X 34" REROD W/CAP	DROVE 1" X 5' GALV PIPE W/ALUM	C-7 DR 1° X 48° PIPE W/DNR CAP IN	10 DR 1" I 48" SALV PIPE I	1/DI C
SET CEDAR POST W/LOC. TAG. " W PINE N55°N 29.9'	DNR CAP. SET CED POST.	HARD WATER BEARING SAND W/6"	CAP & SET CED POST.	11 ALJ
" W PINE NORTH 55.2"	11. N bine N40.e 34'2.	SOIL. DUG-IN SO TOP CED POST W/LOC TAG.		
" N PINE N55°E 31.7'	6" BLK SPRUCE EAST 23.9"	witer indi	7" MAPLE N60°W 3 8" CEDAR N70°E 5	
" W PIME 515°W 60.4'	4" W PINE S45°E 10.0'	9" MAPLE N26"E 1.8"	6" CEDAR S25'E 5	6.7"
REROD \$66*04'E \$2.75'	6" N PINE S15"N 7.2'	9" MAPLE 578°E 13.3"	6" MAPLE S60°N 1	
		12" MAPLE \$20°E 18.0° 9" B CHERRY \$26°N 4.1°	OF MICKE	
117)		CARL	
ned by Lart t. K	Poelr 4-28-9	94 Dale	F. ROSER	
veyor's Michigan License No	12020		SURVEYOR &	
gan alderiou itu		FRAM APPROBATE	MICHIEAN MORE SEARS & GARAGE	IVETORS, JAN. 78, 197 REVISED MAT 14. 107
		· A	PED LAND SURVERENT	REVISED JAN., 190
	<u> </u>		-4444444444444	