

# LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF --:	LOCATED IN --:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 24 N. R. 7 W.	E-8; G-7
2. PROPERTY CONTROLLING IN SECTION	21, T. 24 N. R. 7 W.	10
3. MISCELLANEOUS PROPERTY IN SECTION	T. N. R. E. S. R. W.	
4. LOT NO.	RECORDED PLAT	
5. PRIVATE CLAIMS		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Carl F. Roser, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on May 9, 1979, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on \_\_\_\_\_, 19\_\_\_\_, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. - Description of original monument and accessories and/or subsequent restoration:

C. (continued)

E-8  
 Fd. 7" Cavanagh mon. & raised with 3/4"x14" solid iron rod  
 7" R. Pine N55°E 42.32  
 18" Twin Oak S40°E 71.92  
 6" Cherry S63°W 49.49  
 \*Fd. remains of pine stump N30°E 84.7  
 \*NE Cor. old schoolhouse fdn. S44°W 137'  
 Set cedar post w/loc. tag Due W 30'±  
 \*1909 witnesses by J. G. Cavanagh

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

E-8 Fd. 1 1/4" pipe w/round conc. base per J. G. Cavanagh 1909 survey; corner is 1 1/2' below ground on approximate center gravel road to E & approximately 3' W of center gravel road to S & trail road N.

G-7 Fd. J. G. Cavanagh mon. per 1909 survey. Corner is in line with approximate center of Blacktop road to E & in approximate center of N-S Blacktop road (M-66).

10 Set 1/8 corner per standard B.L.M. instructions.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

G-7 10  
 Fd. 1" pipe in round conc. base (buried 20") raised w/7/8"x20" rerod Drove 5/8"x36" rerod w/RLS Cap  
 5" Oak N15°W 94.39  
 \*SW cor. of old store bldg. N50°E 61.5 6" Triple Maple N77°E 45.37  
 36" Maple N49°W 46.40 11" Twin Maple N45°E 71.43  
 Cor. Fence post S48°E 59.48 Set cedar post w/loc. tag  
 Fence post w/loc. tag Due W 50' Due E 33'  
 \*J. G. Cavanagh 1909 witness

SIGNED BY Carl F. Roser 5-13-81 DATE

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_

CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_

MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. \_\_\_\_\_

MISSAUKEE COUNTY  
 PIONEER TOWNSHIP