

LAND CORNER RECORDATION CERTIFICATE
FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

| FOR CORNERS OF— | LOCATED IN— | CORNER CODE NUMBER |
|---|------------------|----------------------|
| 1. PUBLIC LAND SURVEY..... | T. 24 N. R. 7 W. | E-5; H-9; H-11; I-10 |
| 2. PROPERTY CONTROLLING IN SECTION..... | T. S. R. E. W. | |
| 3. MISCELLANEOUS PROPERTY IN SECTION..... | T. S. R. E. W. | |
| 4. LOT NO., RECORDED PLAT..... | | |
| 5. PRIVATE CLAIMS..... | | |

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Carl F. Roser, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on December 4, 1979, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:
C. (continued)

I-10
Fd. 1 1/4" pipe in conc. raised w/ 5/8"x18" rerod w/RLS Cap
7" Twin Ash N85°E 45.83
Power Pole N85°W 65.25
2" Maple N30°W 68.68
Set cedar post w/loc. tag
Due E 33'

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

E-5 Fd. conc. mon. per J. G. Cavanagh 1909 survey. Corner fd. & accepted by MSHD (RLS J. Wilcox) in 1967 survey. Center of E-W trail road is 2'± south.
H-9 Fd. 2 pieces of round broken conc. & remains of both J. G. Cavanagh witnesses (1909, hemlock 16"S21°E 3.3' & hemlock 24"S54 1/2°W 22.8); at fence corner, fence remains N-W & E. Replaced with DNR monument.
H-11 Fd. conc. mon. & remains of 2 witnesses per J. G. Cavanagh 1909 survey. Old E-W trail road or grade (not drivable) is 20'± north.
I-10 Fd. conc. mon. & one witness (corner fence post S89°E 33') per J. G. Cavanagh 1909 survey. Corner is in line with fences to E & W, & 3'± W of ctr. N-S gravel road.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

| E-5 | H-9 | H-11 |
|-----------------------------------|--------------------------------|--|
| Fd. 2" pipe in conc. (buried 0.5) | Fd. pieces of round conc. | Fd. 1 1/4" pipe in conc; set cedar post w/loc. tag |
| *14" Twin Oak S73°W 33.4 | mon.; set DNR mon. & ced. post | 12" Triple Maple |
| 18" Oak N54°W 77.8 | 7" Maple N40°W 21.4 | N15°W 11.5 |
| *23" Oak Stp. N55°E 48.95 | 12" Maple S70°E 21.9 | 5" Maple S10°W 35.9 |
| *21" Oak S34°E 77.3 | 5" Maple S45°W 10.8 | 11" Twin Maple N70°W 24.0 |
| Fd. Boat spk. Due W 2.6 | | |
| Set ced. post w/loc. tag | | |
| Due N 33 | | |

*MSHD 1967 survey

SIGNED BY Carl F. Roser 5-13-81 DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____

MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

MISSAUKEE COUNTY
PIONEER TOWNSHIP