

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in  
MISSAUKEE  
(County)

Located In:

Corner Code =#

1. Public Land Survey	T 24N. R 07W.	K-3, K-4
	T R	L-5
	T R	
	T R	
2. Property Controlling in Section	S 12 T R	15
	S T R	
3. Miscellaneous Property in Sec.	S T R	
	S T R	

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat  
5. Private Claims

I, CARL T. KIISKILA, in a field survey on JUNE 20, 19 96, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

K-3

K-4

L-5

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													



B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

K-3

K-4

L-5

15

FD. CONSERVATION DEPT. MON FOR NW COR SEC. 12 AS SET BY RLS K.OSTLING IN 1966. OSTLING ACCEPTED FD. CONC-PIPE MON SET BY J.G.CAVANAGH IN 1909. CTR. OF SAND TRAIL ROAD NNW & SE IS 131' +/- 2' WEST.

FD. CONSERVATION DEPT. MON FOR W1/4 CORNER OF SEC. 12. CORNER SET S.P. BY RLS K.OSTLING IN 1966.

RECOVERED OLD 1"X 19" PIPE IN IRREGULAR 5" DIAMETER X 13" CONC. MON FOR N1/4 COR SEC. 13 FD REMAINS OF CAVANAGH'S 1909 ELM BT NW, THAT FITS OK. CTR OF 2-TRACK SOUTH IS 6' WEST. CTR OF E-W SAND ROAD IS 2' SOUTH.

SET REROD W/PS CAP FOR SW CORNER OF SE1/4 OF SW1/4 OF SEC. 12. CORNER SET PER STANDARD BLM INSTRUCTIONS. CTR OF E-W SAND ROAD IS 2' SOUTH. CTR. OF WINDING TRAIL N'LY. IS 96' +/- 5' EAST.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-3

K-4

L-5

15

FD CONSERVATION DEPT MON, ADDED CARSONITE POST.  
3" R.OAK N20°W 26.1'  
\*18" SUG.MAPLE N45°E 36.3'  
4" TW. MAPLE S85°E 16.4'  
4" R.OAK S65°W 31.1'

FD. CONSERVATION DEPT. MON. ADDED CARSONITE POST.  
4" W.ASH N75°W 4.4'  
5" R.OAK NORTH 18.9'  
\*14" SUG.MAPLE N10°E 71.4'  
3" MAPLE N60°E 14.5'  
\*11" TW.B.CHERRY S80°W 28.4'

FD 1" PIPE IN CONC MON.  
15" BEECH(CLP 4) N70°W 38.1'  
16" SUG. MAPLE N50°W 30.3'  
8" SUG. MAPLE N65°E 11.1'  
13" TW.ASH S10°E 47.6'  
SET CARSONITE POST WITH LOCATION TAG NORTH 15'

SET 5/8"x 3/4" REROD W/PS CAP.  
12" SUG.MAPLE N20°W 19.2'  
3" BASSWOOD N30°E 23.6'  
14" TW.SUG.MAPLE S20°E 52.4'  
12" SUG.MAPLE S55°W 37.7'  
SET CARSONITE POST WITH LOCATION TAG SOUTH 33'

\*= RLS K.OSTLING 1966 WIT.

\*= K.OSTLING 1966 WITNESS.

Signed by Carl T Kiiskila Date 7-9-96

Surveyor's Michigan License No. 33981