

LAND CORNER RECORDATION CERTIFICATE
FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF --:	LOCATED IN --:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____ T. <u>24</u> N. <u>8</u> W.		<u>K-7; L-7</u>
2. PROPERTY CONTROLLING IN SECTION _____, T. _____ N. _____ E. _____ S. _____ R. _____ W. _____		
3. MISCELLANEOUS PROPERTY IN SECTION _____, T. _____ N. _____ E. _____ S. _____ R. _____ W. _____		
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND
FILING NUMBER

I, Carl F. Roser, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on February 20, 19 80, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:
K-7 Found 4" railroad rail iron (vertical) as recovered by Dept. surveyor in 1961. Old Cavanagh corner of record (1909).

L-7 Fd. 1/2" x 18" rod, 3'± south of ctr. of E-W gravel road. Corner by RLS, J. Wilcox.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-7	L-7
Fd. 4" r.r. rail (vertical) buried in so. edge of E-W dirt road.	1/2" x 18" rod (buried) inside 3/4" x 24" pipe.
9" R. Pine N42°E 44.76	*12" Cedar N15°E 37.04
4" S. Pine N18°W 52.30	*5" P. Cherry S43°W 16.08
fn Post S12°W 29.15	*Cor fn. post S05°E 32.24
26" Cherry S85°W 289.4	10" Maple N37°W 77.64
ctr. of E-W dirt rd. North 7'±	E-W fn. South 32'±
set ced. post North 40'	fn. South East 3'±
	*Previous Wits

SIGNED BY Carl F. Roser 5-13-81 DATE

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____

MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

BLOOMFIELD TOWNSHIP
MISSAUKEE COUNTY

SURVEYOR'S MICHIGAN REGISTRATION NO. _____