

Montmorency County Remonumentation

Libel 12 Page 42

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

<u>Montmorency</u> (County)	Located In:	Corner Code <u>##</u>
1. Public Land Survey	T <u>29N</u> R <u>1E</u>	<u>A-8</u>
	T <u> </u> R <u> </u>	<u> </u>
	T <u> </u> R <u> </u>	<u> </u>
	T <u> </u> R <u> </u>	<u> </u>
2. Property Controlling in Section	S <u> </u> T <u> </u> R <u> </u>	<u> </u>
	S <u> </u> T <u> </u> R <u> </u>	<u> </u>
3. Miscellaneous Property in Sec.	S <u> </u> T <u> </u> R <u> </u>	<u> </u>
	S <u> </u> T <u> </u> R <u> </u>	<u> </u>

RECEIVED
MONTMORENCY COUNTY
REGISTERED
DEC 28 9 05 AM '93
A. P. MASON-MCELROY

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, Larry G. Beauregard in a field survey on May, 19 93, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

- (A-8) GLO Post set by John Hodgson May 1839.
Wits: Pine 6" N 49° W 18 links Aspen 6" S 34° W 6 links
G.F. De La Mater P.S. # 693 (Otsego Co. Surveyor) in 1933 fnd. Post & one B.T. & set 1/2" x 30" bar. Wits marked: (W. Oak 6" N 17 1/2° E 55.4') (W. Pine stp. S 53° W 53.2').
Frank N. Smith P.S. #703 in 1944 didn't find Post or bar by De La Mater but did find one wits & re-set Cor. & wits: (W. Pine stp. S 53° W 53.2') (3" Oak N 57° E 39.7').
Norman C. Caldwell P.S. #12018 in 1968 found 1/2" bar (No wits) (Survey in 24, T29N, R1W, & in Sec. 19, T29N, R1E).
Donald E. Sagasser P.S. #14770 in 1983 (Otsego Co. Rd. Comm. Surveyor) fnd. 1/2" bar & wits marked: (12" W. Pine N 73° E 36.33') (20" W. Pine S 39° E 46.09') (4" Conc. Mon. S 88° E 33.04') (Meridian Line Rd. Survey).
Sagasser also re-set 1/2" pipe in Mon. box in 1984 after construction & paving of Meridian Line Rd. Survey.
Larry G. Beauregard P.S. #18654 (Scott Assoc.) in 1987 & 1992 fnd. 1/2" pipe in Mon. box (No I.D. cap). Survey in Sec. 24, T29N, R1W & Survey in Sec. 19, T29N, R1E. Wits: (S 88° E 33.04' Conc. Mon. (R)) (S 39° E 46.09' 20" W. Pine) (No Act 74 on file).

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

- (A-8) Fnd. 1/2" pipe in Mon. box on the C/L of Meridian Line Rd. (No I.D. cap).
(Placed 3" dia. Aluminum cap marked Montmorency Co. Re-Mon. Cor. on same.)

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

- (A-8) 1/4 Cor. Comm. to Sec. 19, T29N, R1E & Sec. 24, T29N, R1W
1/2" pipe & Re-Mon. cap #18654 in Mon. box. Accepted as a perpetuation of the original government corner, approved by the Peer Group on September 24, 1993.
S 88° E 33.05' Conc. Mon. (Placed P.S. cap #18654 on same.)
N 50° E 64.11' Tw. 5" & 8" Maples (Placed 20 penny spike & P.S. tag #18654) (typ)
S 80° E 63.63' 12" W. Pine
East 36.76' T. Pole

Signed by Larry G. Beauregard Date 12-27-93
Surveyor's Michigan License No. 18654

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 1985

