

# SURVEY & REMONUMENTATION

FEB 06 1998

Montmorency County Remonumentation

Liber 00012 Page 0285

## SECTION

## LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

MONTMORENCY  
(County)

ALBERT TWP.

Located In:

Corner Code ~~##~~

1. Public Land Survey

T 29N R 1E

G - 12

T R

T R

T R

2. Property Controlling  
in Section

S T R

S T R

3. Miscellaneous  
Property in Sec.

S T R

S T R

STATE OF MICHIGAN  
MONTMORENCY COUNTY  
Recorded & Filed

12-16-1997 10:51:55

A. PANGAN-MCELROY  
REGISTER OF DEEDS

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat

5. Private Claims

I, DONALD E MARLATT, in a field survey on 6/10, 19 97,  
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned  
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the  
current manual of survey instructions of the United States Department of the Interior, Bureau of Land  
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5  
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a  
Court of Law; established, re-established, monumented, re-monumented, recovered, found as  
expressed below:

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded  
on this certificate.**

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

A. Description of original monument and accessories and/or subsequent restoration:

G - 12, 1/4 CORNER COMMON TO SEC.'S 33 & 34.

GLO CORNER SET LEWIS CLASON APRIL 1840. MARKED Y.PINE 28" FOR 1/4 POST.

F. SMITH NOTES. G. DELAMATER WIT. W.OAK 5" S39°45'W 21.5', B. OAK 6" N75°W 18.8'.

SURVEY BY N.C.CALDWELL FEB. 12, 1971 & SEPT 14, 1968. (FD. MONUMENT & MARKED WIT. BELOW).

SURVEY BY R.S.SCOTT ASSO. INC. 8/8/77. L. 2, P. 236. FOUND RECORD MONUMENT.

ACT 74 BY L. BEAUREGARD 6-14-79. L. 1, P. 318. FD. CONC. MON. N43°E 7.3' 6"OAK

S45°E 18.2' 6"OAK, S48°W 17.5' 9"OAK.

SURVEY BY R.S.SCOTT ASSO. INC. 8/27/79. L. 2, P. 567. (SAME COR. & WIT. AS ABOVE).

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

G - 12 1/4 COR. COMMON TO SEC.'S 33 & 34.

FOUND CONC. MON. (R)

N45°E 10"OAK 7.12' (BEAUREGARD WIT.)

S34°E 12"OAK 18.14' "

S57°W 13"OAK 17.5' "

WEST 14"OAK 28.05'

APPROVED BY  
PEER GROUP

JUN 20 97

*D.E.B.*

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

G - 12 1/4 CORNER COMMON TO SEC.'S 33 & 34.

PLACED REMON. CAP ON CONC. MONUMENT.

N45°E 10"OAK 7.12'

S34°E 12"OAK 18.14'

S57°W 13"OAK 17.5'

WEST 14"OAK 28.05'

WITNESSES MARKED WITH 40 PENNY SPIKES AND P.S. TAGS # 18660.

APPROVED BY PEER GROUP JUNE 20, 1997 AS THE BEST AVAILABLE EVIDENCE OF THE POSITION  
OF THE ORIGINAL CORNER.

Signed by Donald E Marlatt

Date 12/15/97

Surveyor's Michigan License No. 18660

