LAND CORNER RECORDATION CERTIFICATE						
For	corners in		Filing Requirem	ent of Act 74, Mich. P.A.	1970 Liber 00012 Page 0304	
			Laure All		ELIGI WITH THE MAN COUNTY OF THE PARTY	
	Montmorency ()	<u>y </u>	Located In: Albert Twp.	Corner Code #	STATE OF MICHIGAN	
1. 8	Public Land	l Survey	T 29N R 1 E	M.P.#13	MONTMORENCY COUNTY	
	abilo caria		TR (1001 1010	Recorded & Filed	
			TR TR		08-25-1998 11:05:43	
	Property Co	ontrolling	S T R		MARY JO BUEST	
,	in Section		S TR		REGISTER OF DEEDS	
3. N	Miscellaneo	us	S TR		Register of Deeds Stamp & File Number	
Property in Sec. S						
	T R Montmorency County Remonumentation					
4. Lot No, Recorded Plat A B C D R F G H I J K L M						
5. Private Claims						
					3	
					4 -7 - 8 - 9 - 10 - 11 - 12 - 5	
I, Larry G. Beauregard , in a field survey on April , 1998 , 1998						
do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the						
current manual of survey instructions of the United States Department of the Interior, Bureau of Land 8 19 20 21 22 23 24 Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and						
5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below: 10 30 29 28 27 26 25						
			ers, all in the same town and range	•	11	
		s certificate.	not me at also settle could enter retific	, may so reconact	12 31 32 33 34 35 36	
A.	Description restoration	_	al monument and accessorie	es and/or subsequent	13 to decide the last of the l	
	M.P. #13 Corner Common to Section 28 & 29 on the North shore of West Tw. Lake, T29N R1E					
	1939 - Lewis Clason D.S. Set post. Wit's mkd (Spr. Pine 7" N28W 29lks)(Spr.Pine 8" N78E 22lks) 1913 - Frank N. Smith RLS#754 - Prepared the Plat of Herman Lunden's Sub. Royola on Section's 28, & 29. Rec. L. 1, of Plats Pg. 10					
	that mentions a Iron Meander Stake on Lake Shore in line between Sec.'s 28, & 29. (No wit's mkd.) 1926 - Frank N. Smith RLS#754 - Prepared the Plat of Lester Lunden's Sub. in Sec. 28. Rec. L, 1 of Plats Pg. 23 & makes no mention					
	of MP on Section line between Sec.'s 28, & 29.					
	1951 - Frank N. Smith RLS#754 - Prepared the Plat of Lester Lunden's Moccasin Trails Subdivision in Sec's 20 & 29. Rec. L. 1 of Plats pg. 44. & makes no mention of MP on Section line between Sec's 28, & 29.					
B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:						
	April 1998 - Didn't find Iron stake & Plat mon. falls in lake. Placed 4"dia. x 36" conc. mon. & Re-mon cap on Section line.					
	NOTE: This reference mon. would be 50.83'ft. North of GLO M.P. ALSO NOTE: Peer Group recommended that I file a Act 132 that would show how monumented M.P. relates to Plat					
		boundaries.				
C.	Description of monument for corner and accessories established to perpetuate locating the position of the corner:					
	M.P. #13 Corner Common to Section 28, & 29 on the North Shore of West TW. Lake, T29N R1E.					
	3 1/2" Aluminum Re-mon cap on 4"dia. concrete Mon.					
	Accepted as the best available evidence of the original corner and that the recommendation of the contracter be accepted. Approved by the Peer Group on July 28, 1998.					
	East 31.89' 19"Norway (Placed 60d spike & Ps tag#18654.)(Typ.) Act #132 Rec. L. 10005, P. 0010					
	-	3.10' 26"W.P		и	•	
		3.55' 8"Birch		11		
Signe	<i>,</i>	Ja	ny Speanogene	Date	8-24-98	
Surveyor's Michigan License No. 18654 FORM APPROVED BY MICHIGAN STATR BOARD OF PROFESSIONAL						
	SURVEYORS, JAN 28, 1971 REVISED MAY 14, 1975 REVISED JAN, 1983 REVISED OC, 1995					
			A. I. G.	SURVEY &	APPROVED BY	
			BEAUREGARD C	EMONUMENTATION	PEER GROUP	
			SURVEYOR 5 NO. 18654	OCT 0 8 1998	JUL 2 8 98	
			OB POFESSIONAL STE		f.B.B.	
() ·			OFESSIONA	SECTION	<i>v</i>	