

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:
Montmorency Located In Corner Code #
(County)

1. Public Land Survey T 29N R 2E L-5
T
2. Property Controlling in Section S 13 T 29N R 2E 9
S T R
3. Miscellaneous Property in Section S T R
S T R

4. Lot No: Recorded Plat:

5. Private Claims:

I, Carl T. Kiiskila, in a field survey on May 25, 2004 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	5		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

L-5 G.L.O. Lewis Clason 1839 Set quarter section post
Wit: Y. Pine 22" S60°W 53 links
Spruce Pine 9" N53°E 57 links

9- This corner position was not established during the original government survey.

Liber 1, Page 495 Norman J. Quaine LLS #33984 Found
a 4" pipe and State of Michigan Cap
Wit: S30°E 12.91' 3" Cherry
S73°W 27.31' 6" Aspen
N78°W 30.57' 18" Aspen
N54°W 28.54' 12" Aspen

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

L-5 Found State of Michigan monument as witnessed by Norman J. Quaine.

9- Established the Southwest corner of the Southeast quarter of the Northeast quarter of section 13 as per B.L.M. instructions for the subdivision of a section.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

L-5 State of Michigan monument
Wit: 24" Aspen N80°W 30.50'
8" R. Pine S20°W 106.00'
10" R. Pine S47°E 129.81'
8" Maple clump N13°W 77.97'
Blue Carsonite Post North 1'±

9- Set a 5/8" X 32" rerod with P.S Cap #33981
Wit: 5" Maple N84°E 6.36'
5" Balsam S11°E 30.42'
12" Balsam N52°W 5.91'
8" Balsam S22°W 42.89'
Blue Carsonite Post North 1'±

Signed by:

Carl T. Kiiskila

Date:

6-2-04

Surveyor's Michigan License No.:

33981

