

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In: Montmorency Located In Corner Code #
(County)

1. Public Land Survey T 29N R 2E K-7
T 29N R 2E L-7

2. Property Controlling in Section S T R
S T R

3. Miscellaneous Property in Section S T R
S T R

4. Lot No: Recorded Plat:

5. Private Claims:

I, Carl T. Kiiskila, in a field survey on May 25, 2004 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

K-7 G.L.O. Lewis Clason 1839 set post corner sections 13, 14, 23 and 24.

Wit: Y. Pine 16 S69°W 54 links
Spruce Pine 8" N45°E 67 links

L-7 G.L.O. Lewis Clason 1839 set quarter section post

Wit: Y. Pine 20" N57°E 23 links
Y. Pine 16" S32°W 25 links

Liber 1, Page 495 Norman J. Quaine LLS #33984 set a 1/2" rod with P.S. cap #15410 by double proportion.

Wit: S85°W 13.62' 14" Oak
S08°W 16.42' 5" R. Pine
N08°E 4.60' 10" Aspen
N71°E 22.87' 10" Aspen

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

K-7 Found 1/2" iron with P.S. cap # 15410

L-7 Found 3" pipe filled with concrete with a 1/2" pin in the center.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-7 Set 1" X 32" pipe with standard DNR aluminum cap

Wit: 14" Maple Clump S80°W 13.54'
9" R. Pine S10°W 16.57'
7" R. Pine N18°W 47.55'
10" R. Pine S80°E 40.57'
Blue Carsonite Post North 1'±

L-7 3" Pipe filled with concrete with a 1/2" pin in the center

Wit: 7" Oak S46°E 11.20'
4" W. Pine N75°W 14.67'
14" R. Pine N43°E 20.44'
4" W. Pine N35°W 43.59'
Blue Carsonite Post North 1'±

Signed by:

Carl T. Kiiskila

Date:

6-2-04

Surveyor's Michigan License No.:

33981

