## SURVEY & REMONUMENTATION

## Montmorency County Remonumentation

APR 2 4 1995

## LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1976 iber

For	COMMISS	ION	•				
MO	NTMORENCY (County)	Located III.	Corner C	ode ##			
1,	Public Land Survey	I <u></u> H.	APPROVE	DBY	STATE OF M MONTMORENC Recorded &	Y COUNTY	
	Property Controlling In Section Miscellaneous Property in Sec.	T R S T R S T R S T R S T R	AUG 0 5	94 \$\mathcal{B}\$ = \$\mathcal{F}\$	10-19-1994 A. PANGAN- REGISTER 0	MAEL DAY	
4.	Lot No	Recorded Plat		1	A B C		
I, _ do in I cur Ma abo Co exp NC	FREDERICK J. KING hereby certify that under reines 1 and 2 above were rent manual of survey instragement or by a decree of overwere in conformance vourt of Law; established, pressed below:  OTE: Not more than 4 on this certificate	, in a field survey on Acquirements of P.A. 74, Mici in conformance with regular fructions of the United State of Acourt of Law and/or that with the rules of the Michigare-established, monume corners, all in the same a.	higan P.A. of 1970, the constitutions and rules therefores bepartment of the interest the corner points mention an Board of Land Surveyonted, re-monumented, re-town and range, may	, 19 94 ner points mentioned re as required in the erior, Bureau of Land ned in lines 3, 4 and 5 ors or by a Decree of a recovered, found as	2 6 3 4 5 6 7 8 19 9 10 30 11 12 31 13	-17	22 - 27 24 34 3
ν-1		al Post set by Lewis	Clawson, D.S.	N71W - Hemloc N52E - <b>Hem36</b> 5	k - 12.84' k - 10.56'	(19 ]ks) (16 ]ks)	\$ 1.00
	COR. D-1 DNR Mo T28N-R3E NO Ref NOTE:	4 Rec. Bk.1, Pg 59, C n set by KJJ. Ostling made to Cor D-13 (29 - Since Rec shows Cor and Cor D-1 (28-3) RECORDED FOR THIS COR	g, PS #10068 3-3) r C-13 (29-3) to be should be common co		ch - 13.85' leas.	AND Cor E	-13 (29-3)
	Description of corner 3 SOUTH 1/4 CORNER,	evidence found and/or SECTION 32	method applied in res	toring or reestablish	ing corner;		
	8-3-94 - Fnd Rec	<del></del>	_	d Blz in Rec Beech ind Blz in Rec Beec		, ,	
			No 1839 Wit Fnd				

This Corner Approved By County Peer Review on Aug. 5, 1994, as the Best available evidence of the Re-Establishmu of the Original Corner

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

D-13 SOUTH 1/4 CORNER, SECTION 32

8-3-94 - Rec DNR Pipe & Cap

Set Treated 2"x4" Aleng side

THIS COR IS COMMON FOR BOTH D-13, T29N-R3E & D-1, T28N-R3E

N35<sup>O</sup>E - 27.12' - Set Tag in NW side 10" Maple

S650E - 6.46' - Set Tag in N side 8" Beech

S70°W - 6.22' (R-16.05') - Set Tag in SE side 12" Beech

N50°W - 13.82' (R-13.85') - Set Tag in SW side 12" Beech

Surveyor's Michigan License No. 25852

Date <u>10-18-94</u>



FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAH. 2
REVISEO MAY S