

Montmorency County Remonumentation

LAND CORNER RECORDATION CERTIFICATE Liber 00012 Page 0174  
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Montmorency (County) Located In: LOUD TWP. Corner Code # H-1

1. Public Land Survey	T 29N	R 3E	H-1
	T	R	
	T	R	
	T	R	
2. Property Controlling in Section	S	T	R
	S	T	R
3. Miscellaneous Property in Sec.	S	T	R
	S	T	R

STATE OF MICHIGAN  
MONTMORENCY COUNTY  
Recorded & Filed

11-21-1995 13:21:24

A. PANGAN-MCELROY  
REGISTER OF DEEDS

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat  
5. Private Claims

I, Donald E. Marlatt, in a field survey on 4-24-1995, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:  
(H-1) N. 1/4 corner of Section 3, T 29 N, R 3 E.  
None. NO CORNER SET ON ORIGINAL SURVEY

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(H-1) N. 1/4 corner of Section 3, T 29 N, R 3 E.

Set concrete monument and remonumentation cap by S.P. method on South line of Section 34, T 30 N, R 3 E.  
5.45' East of the South 1/4 corner of Section 34, T 30 N, R 3 E.

SURVEY &  
REMONUMENTATION

DEC 18 1995

COMMISSION

APPROVED BY  
PEER GROUP

JUN 02 95

L. J. B.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(H-1) N. 1/4 corner of Section 3, T 29 N, R 3 E.  
Set concrete monument and remonumentation cap #18660.  
S 19\* W Power Pole 36.3'  
S 64\* W 11" Balsam 18.79'  
N 57\* E 9" Scotch Pine 72.82'  
N 17\* E 8" Maple 78.78'  
20' South of centerline.  
Witnesses marked with 30" penny spikes & P.S. tag #18660.  
Approved by the Peer Group on June 2, 1995 as a careful and faithful establishment of the position of the corner.



Signed by Donald E. Marlatt Date 11-7-1995  
Surveyor's Michigan License No. 18660