

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. PA 1970

For Corners In: Montmorency (County) Located In Corner Code #
1. Public Land Survey T R
2. Property Controlling in Section S T R
3. Miscellaneous Property in Section S 27 T 30 N R 02E 8
S 27 T 30 N R 02E 11

4. Lot No: Recorded Plat:
5. Private Claims:

I, Carl T. Kiiskila, in a field survey on October 20 2010 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

Register of Deeds Stamp & File Number

Table with 13 rows and 13 columns (A-M). Contains numbers 1-36 and a central point marked with a dot at row 10, column H.

A. Description of original monument and accessories and/or subsequent restoration:

8 - CW 1/16 Corner of Section 27, T30N,R02E 11 - SW 1/16 Corner of section 27, T30N,R02E
None None

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

8 - CW 1/16 Corner of Section 27, T30N,R02E 11 - SW 1/16 Corner of section 27, T30N,R02E
Set stamped 2" dia. aluminum cap on 5/8"x34" rebar per standard BLM procedure. Corner falls 7' south of C/L of an old E-W road bed. Found no other evidence to dispute the location for the corner.
Set stamped 2" dia. aluminum cap on 5/8"x34" rebar per standard BLM procedure. Found no other evidence to dispute the location for the corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

8 - CW 1/16 Corner of Section 27, T30N,R02E 11 - SW 1/16 Corner of section 27, T30N,R02E
Stamped 2" dia. alum. cap on 5/8"x 34" rebar Stamped 2" dia. alum. cap on 5/8"x 34" rebar
Wit: N38°E 38.66' to set N&T on E side 5" R. Maple S74°E 33.07' to set N&T on N side 24" Oak S30°W 16.60' to set N&T on SE side 5" R. Maple N53°W 38.89' to set N&T on NE side 11"&17" Twin R. Maple Set Blue Carsonite post w/ location tag 1' North
Wit: N30°E 24.95' to set N&T on NW side 12" R. Maple S34°E 10.03' to set N&T on SW side 13" R. Maple S77°W 32.64' to set N&T on S side 9" R. Maple N24°W 21.64' to set N&T on W side 5",8"&12" Triple R. Maple Set Blue Carsonite post w/location tag 1' North.

Surveyor's Michigan License No.: 33981



12-27-10