

# SURVEY & REMONUMENTATION

JAN 22 2001

Montmorency County Remonumentation Liber 00012 Page 0436

## SECTION

### LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

MONTMORENCY  
(County)

Located In: BRILEY TWP.

Corner Code #

1. Public Land Survey

T 30N R 2E C-2

2. Property Controlling  
in Section

S T R

3. Miscellaneous  
Property in Sec.

S T R

STATE OF MICHIGAN  
MONTMORENCY COUNTY  
Recorded & Filed

Recorded in Montmorency County  
Date: 12-05-00 Time: 10:04  
*Laura Wilson* Register of Deeds

Register of Deeds Stamp & File Number

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_

5. Private Claims \_\_\_\_\_

I, DONALD E MARLATT, in a field survey on MAY 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

#### A. Description of original monument and accessories and/or subsequent restoration:

C-2 1/4 COR. COMMON TO SECTIONS 5 & 6

GLO COR. SET BY LEWIS CLASON IN APRIL 1840. BEECH 12" N65°E 35 L., BEECH 10" N68°W 77 L.

D.E. MARLATT PS # 18660 FILED ACT 132 DATED 6/13/80 REC. L. 10005, P. 159. SET 1/2" ROD & CAP SINGLE PROPORTION. N25°W 3.3' 12" MAPLE, S80°W 8" MAPLE 8.0', S20°E 14.3' 4" MAPLE.

D.E. MARLATT P.S. FILED ACT 132 DATED 3/18/81 & REC. IN L. 3, P. 143. COR. & WIT. SAME AS ABOVE

D.E. MARLATT P.S. FILED ACT 132 DATED 8/16/97-REC. L. 10004, P. 512. FOUND 1/2" ROD & CAP. N25°W 12" MAPLE 3.3', S80°W 8" MAPLE 8.0', S20°E 4" MAPLE 14.3', N80°E 6" MAPLE 5.25'.

#### B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

C-2 1/4 COR. COMMON TO SECTIONS 5 & 6.

FOUND 1/2" ROD & CAP #18660

N30°W 14" MAPLE 3.57' R.

S80°W 10" MAPLE 8.1' R.

S10°E 6" MAPLE 14.45' R.

N78°E 7" MAPLE 5.25' R.

APPROVED BY  
PEER GROUP

JUL 18 00

*L.B.B.*

#### C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

C-2 1/4 COMMON TO SECTIONS 5 & 6.

SET CONC. MONUMENT & REMON. CAP.

N30°W 14" MAPLE 3.57'

S80°W 10" MAPLE 8.10'

S10°E 6" MAPLE 14.45'

N78°E 7" MAPLE 5.25'

WITNESSES MARKED WITH 40 PENNY SPIKES AND PS TAG # 18660.

APPROVED BY PEER GROUP ON JULY 18, 2000 AS THE BEST AVAILABLE EVIDENCE OF THE RE-ESTABLISHMENT OF THE POSITION OF THE ORIGINAL CORNER.

Signed by Donald E Marlatt

Date 12/4/2000

Surveyor's Michigan License No. 18660

