

JAN 22 2001

Montmorency County Remonumentation

Liber **00012** Page **0421**

SECTION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

MONTMORENCY Located In: BRILEY Corner Code #
(County)

- | | | |
|-------------------------|---|-----|
| 1. Public Land Survey | T <u>30N</u> R <u>2E</u> | C-8 |
| | T <u> </u> R <u> </u> | |
| | T <u> </u> R <u> </u> | |
| | T <u> </u> R <u> </u> | |
| 2. Property Controlling | S <u> </u> T <u> </u> R <u> </u> | |
| in Section | S <u> </u> T <u> </u> R <u> </u> | |
| 3. Miscellaneous | S <u> </u> T <u> </u> R <u> </u> | |
| Property in Sec. | S <u> </u> T <u> </u> R <u> </u> | |

STATE OF MICHIGAN
MONTMORENCY COUNTY
Recorded & Filed

11-13-2000 13:32:33

TERESA WALKER
REGISTER OF DEEDS

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat
5. Private Claims

I, FREDERICK J. KING, in a field survey on MARCH 21, 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and for that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A	B	C	D	E	F	G	H	I	J	K	L	M
1												
2	6		5		4		3		2		1	
3												
4	7		8		9		10		11		12	
5												
6	18		17		16		15		14		13	
7												
8	19		20		21		22		23		24	
9												
10	30		29		28		27		26		25	
11												
12	31		32		33		34		35		36	

A. Description of original monument and accessories and/or subsequent restoration:


C-8 - 1/4 CORNER COMMON TO SECTIONS 19 & 20

- June 1840-Orig Post set by Lewis Clason, DS -(1)S58°W-22 lks(14.52') 12" Ced (2)N80°E-14 lks(9.24') 8" Spruce - Pg. 455
1941 - 2 1/2" Conc Mon set by Frank Smith, PS#754 -(3)N45°E-50.0'-4" Conc Mkr. (4)S45°W-50.0'-4" Conc Mkr - Info obtained from L.G. Beauregard, PS#18654
- July 1978 - LCRC by R.R. Bischer, PS#22428 - Rec. L. 1, Pg. 225 - Fnd 6" Conc Mon - Set by Briley in 1941 - Wit (3), (4) & (5)N57°W-31.20'-9" Cedar (6)N71°E-10.17'- 8" Cedar
- July 1978 - Witnesses obtained from D.E.Porter-PS#15410-Fnd 6" Conc Mon - 8' W of River Bank - Not Recorded - Same Wit as LCRC Rec. L.1, pg. 225
- Nov. 1987 - Act 132 by L.G.Beauregard, PS#18654 (Surveyor for Scott Eng) - Not Recorded - Exist Conc Mon(R)-Witnesses 3 & 4
- Jan 1991 - Site Sketch by C.R.Johnson, PS#30083 - Not Recorded - Shows Cor Fnd - No Corner Desc. - No Witnesses

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

C-8 - 1/4 CORNER COMMON TO SECTIONS 19 & 20

- Fnd 4" Conc Mon (Rec as 2 1/2" & 6")
Fnd Rec Witnesses #3, #4, #5 & #6



THIS CORNER APPROVED BY COUNTY PEER REVIEW ON JULY 18, 2000, AS THE BEST AVAILABLE EVIDENCE OF THE RE-ESTABLISHMENT OF THE ORIGINAL CORNER.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

C-8 - 1/4 CORNER COMMON TO SECTIONS 19 & 20

- Placed 3 1/4" Aluminum Montmorency County Re-Mon Cap on Fnd 4" Conc Mon * Corner is 1n N-S Fnc & 8' W of W Bank of Barger Creek - Set Treated 2"x4" Alongside.
- (Wit#3) - N45°E - 49.85' (R-50.0') - 4" Conc Mon
- (Wit#6) - N71°E - 9.98' (R-10.17') - Set S&T - N side 10" Cedar * S25°W - 17.49' - Set S&T W side 8" Cedar
- (Wit#4) - S45°W - 50.27' (R-50.0') - 4" Conc Mon
- (Wit#5) - N57°W - 31.29' (R31.20') - Set S&T - SW side 12" Cedar * N05°W - 21.35' - Set S&T - E side 6" Cedar

Typical Wit Set = 16-D Spk & Plastic ID Tag #25852

Signed by Frederick J. King
Surveyor's Michigan License No. 25852

Date October 30, 2000

**APPROVED BY
PEER GROUP**

JUL 18 00

J.L.B.