

# SURVEY & REMONUMENTATION

JAN 22 2001

Liber 00012 Page 0401

## SECTION MONTMORENCY COUNTY REMONUMENTATION LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Located in:

Montmorency  
(County)

Briley  
(Township)

Corner Code #

1. Public Land Survey

T 30N R 2E

C - 9

2. Property Controlling  
in Section

S

T

R

3. Miscellaneous  
Property in Sec.

S

T

R

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_

5. Private Claims \_\_\_\_\_

STATE OF MICHIGAN  
MONTMORENCY COUNTY  
Recorded & Filed

10-27-2000 11:54:06

TERESA WALKER  
REGISTER OF DEEDS

Register of Deeds Stamp & File Number

I, Larry G. Beauregard, in a field survey on MARCH, 20 00, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules thereof as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

C - 9 Section corner common to Section's 19 - 20 - 29 & 30:

1840 Lewis Clason D.S. Set Post Cor. Sec's. 19 - 20 - 29 & 30. Wit's. Mkd. (Cedar 8" S77°W 28 lks.) (Do. 5" N64°E 12 lks.)

1941 Frank N. Smith RLS #754 ran a random line between Sec's. 20 & 29 & intersected 30.3' North of Old stake & most likely set 2" pipe at stake location for corner. No Wit's. Mkd.

1960 Leo R. Smith RLS #10706 (Surveyor for Scott Eng.) Fnd. pipe & accepted its position in a section divisional survey of Sec. 30. No Wit's. Mkd.

1978 Ronald R. Bischer P.S. #22428. (Surveyor for Porter's Survey). Fnd. 2" pipe by old 4" sq. stake. Filed LCRC Rec. L. 1, P. 225. Wit's. Mkd. (N18°W 54.76' 6" Spruce) (N50°E 37.47' 9" Birch) (S36°W 29.16' 18" Birch)

1978 Delmer E. Porter P.S. #15410. Fnd. 2" pipe & 4" sq. stake. Filed Act #132. Rec. L. 2, P. 443. Wit's. Mkd. (N50°E 37.47' 9" Birch) (S36°W 29.16' 18" Birch)

1987 Larry G. Beauregard P.S. #18654. (Surveyor for Scott Assoc. Inc.) Fnd. 2" pipe & 4" sq. stake at corner, accepted its position in a section divisional survey of Sec. 20. Also fnd. all Wit's by Bischer. Prepared Act #132 for boundary Survey in Sec. 20. (Not recorded & no new Wit's. Mkd.)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

March 2000: Fnd. 2" pipe, 4" sq. stake & Wit's. by Bischer. Re-placed pipe with 4" x 36" concrete monument with a 3/4" aluminum Re-mon. cap on top.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

C - 9 Section corner common to Section's 19 - 20 - 29 & 30.

4" x 36" concrete monument with a 3/4" aluminum Mont. Co. Re-mon. cap.

Accepted as a perpetuation of the original government corner.

Accepted by the peer group on July 18, 2000.


N 49° E 37.47' 11" Birch in clump

S 34° W 29.16' 18" Birch

N 28° W 113.85' 15" Cedar

North 54.76' 10" Spruce

Placed 60d penny spike & P.S. tag #18654 (typ).



APPROVED BY  
PEER GROUP

JUL 18 00

*LGB*

Signed by Larry G. Beauregard

Date 10-27-00

Surveyor's Michigan License No. 18654

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971  
REVISED MAY 14, 1975  
REVISED JAN. 1983  
REVISED OCT. 1995