

# SURVEY & REMONUMENTATION

JAN 22 2001

Liber 00012 Page 0407

SECTION

## MONTMORENCY COUNTY REMONUMENTATION LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Located in:

Montmorency  
(County)

Briley  
(Township)

Corner Code #

1. Public Land Survey

T 30N R 2E

E - 9

2. Property Controlling  
in Section

S

T R

3. Miscellaneous  
Property in Sec.

S

T R

4. Lot No. , Recorded Plat

5. Private Claims

STATE OF MICHIGAN  
MONTMORENCY COUNTY  
Recorded & Filed

10-27-2000 11:55:36

TERESA WALKER  
REGISTER OF DEEDS

Register of Deeds Stamp & File Number

I, Larry G. Beauregard, in a field survey on MARCH, 2000, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules thereof as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

E - 9 corner common to Sections 20 - 21 - 28 & 29:

- 1840 Lewis Clason D.S. Set Post Cor. Sec's. 20-21-28 & 29. Wit's. Mkd. (Cedar 7" N57°E 10 lks.) (Dd. 9" S55°W 14 lks.)  
1935 From Frank N. Smith note book a Cedar Post was established or fnd. by Grove Stevens (Circa 1920) 11' North of est. A.M. Rouse (Circa 1900).  
Wit's. Mkd. (Blazed Cedar 12" S70°30'W 3.25') (Cedar 6" S03°30'E 10') (Blazed Cedar 12" S13°45'E 12.7')  
(Cedar 14" S59°30'W 21')  
1941 Frank N. Smith RLS #754. Fnd. Cedar stake & set 2 1/2" concrete monument at corner. Wit's. Mkd. (N45°E 50' 4" dia. concrete monument) (S45°W 50' 4" concrete monument)  
1974 Delmer E. Porter P.S. #15410. Fnd Conc. Mon. by Fe. Cor. & Filed LCRC Rec. L. 1, P. 108. Wit's. Fnd. (N45°W & S45°E 50' Conc. Mon.) Mkd. (S60°W 18.31' 20" Cedar) (North 32.35' 9" Cedar)  
1978 Donald E. Marlatt P.S. #18660. Fnd. corner. (No description for corner or Wit's. mentioned on Act #132. (Not recorded)  
1980 Donald E. Marlatt P.S. #18660. Fnd. monument at corner, Wit's. by Porter & Wit's. mon's. N45°W & S45°E 50' by Smith. Filed Act #132. Rec. L. 3, P. 81. No new Wit's. Mkd.  
1993 Eugene D. Farrier P.S. #24594. Fnd. corner. (No description for corner or Wit's. mentioned on Act #132. Rec. L. 362, P. 102.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

March 2000: Fnd. 2 1/2" concrete mon., at corner, Wit's. & Mon's. by Smith & Wit's. by Porter. Placed a 3 1/2" aluminum Re-mon. on top cap.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

E - 9 corner common to Sections 20 - 21 - 28 & 29.  
2 1/2" concrete monument with a 3 1/2" aluminum Mont. Co. Re-mon. cap.

Accepted as a careful and faithful establishment of the position of the corner.

Accepted by the peer group on July 18, 2000.


N 45° W 50.00' Fnd. 4" Conc. Mon. (R)  
S 45° E 50.00' Fnd. 4" Conc. Mon. (R)  
S 60° W 18.31' 20" Dbl. Cedar (R)  
North 32.35' 13" Cedar (R)

Placed 60d penny spike & P.S. tag #18654 (typ).

Note: Conc. Mon. at S45°E is ± 22' above grd., base dist. to cor.  
checks. Top dist. from center of mon. is ± 50.35' to cor.

APPROVED BY  
PEER GROUP

JUL 18 00 L.B.B



Signed by Larry G. Beauregard Date 10-27-00

Surveyor's Michigan License No. 18654