

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:

Montmorency

(County)

Located In

Corner Code #

1. Public Land Survey

T

R

T

R

2. Property Controlling
in Section

S 28

T

30N

R

2E

14

S 28

T

30N

R

2E

16

3. Miscellaneous
Property in Section

S

T

R

S

T

R

4. Lot No:

Recorded Plat:

5. Private Claims:

I, Carl T. Kiiskila, in a field survey on April 28, 2001 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

14-Kenneth J. Ostling RLS # 10068 Sept. 1977 set 5/8" iron bar w / RLS cap.

16- Kenneth J. Ostling RLS # 10068 Sept. 1977 set 5/8" iron bar w / RLS cap.

Wit: 20" Oak N77°W 27.1'
23"Oak N20°W 65.8'

Wit: 17" Oak N78°E 38.7'
23"Oak N51°W 26.2'
center E-W RD. South 6'
cedar post North 12'

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

14- Found 5/8" rod.

16- Found 1/2" rod with P.S. cap #18654 L. Beauregard.



C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

14- Found 5/8" rod

Wit: 16" twin Oak N78°E 65.67'
Power Pole N33°E 69.95'
24" twin Oak N18°W 66.00'
22" Oak N73°W 27.74'
Center line of Co. Rd. 489 East 2'±

16 Found 1/2" rod with cap

Wit: *Power Pole N58°W 58.98'
24" Oak N78°E 39.40'
22" Oak S40°E 61.69'
18" Oak S13°W 41.02'
Center line Co. Rd. 489 South 4'±
Carsonite post South 33'±

* Old witnesses by others

Signed by:

Carl T. Kiiskila

Date:

2-7-02

Surveyor's Michigan License No.:

33981