DUED DECORDATION CERTIFICATE

	Filing Requir	rement of Act 74, Mich. P.A	L 1970	
For corners in	•	1		
Montmorency	Located In:	Corner Code ##		
(County)				
1. Public Land Survey	T 31N R 2E T R T R	<u>G-10</u>		
 Property Controlling in Section Miscellaneous Property in Sec. 	T R S _27_ T 31N_ R 2E S T 31N_ R 2E S T R S T R	11	Register of Deeds Stamp & File Number	
•			A B C D E F G H I J K L	L
4. Lot No	Recorded Plat			Ţ
5. Private Claims			2 - 6 5 - 1 - 1 - 3 2	ì
			3	Ţ
			4 - 7 - 4 - 9 - 10 - 11 - 11	1
Carl R. Johnson	_ , in a field survey onMay	7 14, 19 90	5	Ţ
do hereby certify that under r	equirements of P.A. 74, Michigan 1	and rules therefore as required in	n the	Ï
do hereby certify that under requirements of P.A. 74, michigant and rules therefore as required in the in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the interior, Bureau of Land current manual of survey instructions of the United States Department of the interior, Bureau of Land				1
Management or by a decree (of a Court of Law and/or that the cor	ner points mentioned in lines 3, 4 a.	ind 5 8 19 20 21 22 23 1	1
Management or by a decree of a Court of Law and/or that the confer pointed and Surveyors or by a Decree of a above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a court of Law; established, re-established, monumented, re-monumented, recovered, found as				Ţ
avaraged below.				-z
NOTE: Not more than 4	corners, all in the same town	and range, may be recorded		7
on this certificat	te.		12 31 32 33 34 35 5	-3:
	al monument and accessories a	and/or subsequent restoration:	13 <u> </u>	

- B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:
 - Set midway and on line between section corners. Falls on edge of red pine plantation G-10 line north and east.
 - Set by standard survey procedure for subdivision of a section. 11
 - Set by standard survey procedure for subdivision of a section. 12

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner: 12 S1/8 Corner on N-S 1/4 Line Manual Internation G-10 W1/4 Corner Set 5/8" Bar with cap 9" Cedar N60 W 20.8ft 10" Cedar S49 E 17.8ft Set DNR Monument 10" Red Pine N45°E 6.8ft 4" White Pine S53°E 52.1ft CARL R NOZNHOL 9" Cedar S45°W 25.0ft 6" Aspen S14°W 36.2ft LAND URVEYOR 11 Center of SW 1/4 30083 Set 5/8" Bar with cap 5" Cherry S11 W 36.0ft SEO LAND 4" Cherry N25°W 9.1ft

Signed by 30083 FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971 Surveyor's Michigan License No. REVISED MAY 14, 1975 REVISED JAN., 1983