

MAY 16 1997

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

STATE OF MICHIGAN
MONTMORENCY COUNTY
Recorded & Filed

11-01-1996 09:42:08

A. PANGAN-MCELROY
REGISTER OF DEEDS

Register of Deeds Stamp & File Number

For corners in
MONTMORENCY
(County)
1. HILLMAN TWP.
Public Land Survey
Located In: T 31N R 4E Corner Code E - 13
T R
T R
T R
2. Property Controlling S T R
in Section S T R
3. Miscellaneous S T R
Property in Sec. S T R
4. Lot No. , Recorded Plat
5. Private Claims

I, DONALD E. MARLATT in a field survey on 7 - 1, 19 96,
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the
current manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
Court of Law; established, re-established, monumented, re-monumented, recovered, found as
expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

E - 13 SOUTH CORNER COMMON TO SEC'S 32 & 33
CORNER SET BY LEWIS CLASON 3-18-1839.
CEDAR 7"-N42°W-32', W. BIRCH 4"-N56°E-13
ACT 74 BY D. PORTER L. 1, P. 80, 1-4-1974. FOUND 1 1/4" PIPE.
N85°W-25.6' 8" POPLAR, S30°W 24.83' 12" POPLAR, S25°E 25.68' 12" POPLAR
DNR SURVEY 1982. FOUND 1 1/4" PIPE. SURVEY REPORT IN FILE.
D.E. MARLATT SURVEY 10-1-1987. FOUND 1 1/4" PIPE.
WEST 25.5' 16" POPLAR, S25°W 24.6' 17" POPLAR, S50°E 25.4' 17" POPLAR.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

E - 13 SOUTH CORNER COMMON TO SEC'S 32 & 33.
FOUND 1 1/4" PIPE
S36°W 17" POPLAR 24.52'
N 85°W 18" POPLAR 25.45'
S45°E 18" POPLAR 25.52'

NORTH 1/4 COR. OF SEC. 4, T30N, R4E IS 42.82' WEST.

NOTE MSHD SURVEY DATED 4-5-1966 WAS NOT ACCEPTED FOR CORNER POSITION.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:


E - 13 SOUTH CORNER COMMON TO SEC'S 32 & 33, T31N, R4E. PLACE REMON. CAP ON 1 1/4" PIPE.
S36°W 17" POPLAR 24.52'
N85°W 18" POPLAR 25.45'
S43°E 18" POPLAR 25.52'
N50°E 8" CHERRY 12.77'

WITNESSES MARKED WITH 30 PENNY SPIKES AND P.S. TAGS#18660.
APPROVED BY PEER GROUP JULY 12, 1996 AS THE BEST AVAILABLE EVIDENCE OF
THE POSITION OF THE ORIGINAL CORNER.

APPROVED BY
PEER GROUP

JUL 12 96

J.S.B.



Signed by Donald E. Marlatt

Date 10/28/96

Surveyor's Michigan License No. 18660