

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

MONTMORENCY

(County)

Located In:

Corner Code #

1. Public Land Survey

T 32N R 2E E-10
T R
T R
T R
T R
S 21 T R 10
S T R
S T R
S T R

2. Property Controlling
in Section

3. Miscellaneous
Property in Sec.

4. Lot No. , Recorded Plat
5. Private Claims

CARL KIISKILA

JUNE 8 97

I, , in a field survey on , 19 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

10

E-10

(NO EVIDENCE OF G.L.O. CORNER, B.T.'S, LINE TREES & TOPOGRAPHY, AS CALLED OUT IN THE G.L.O. LINE NOTES; UNLESS NOTED IN ITEM "B" BELOW.)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

10

RESET MARCUS SCHAAF'S 1 1/4" PIPE WITH CONC. BASE FOR THE NW CORNER OF THE SW 1/4 OF THE SW 1/4 SEC 21 TO FIT STANDARD BLM INSTRUCTIONS FOR SUBDIVISION OF A SECTION. N-S SMOOTH WIRE IS 1' EAST.

E-10

ADJUSTED MARCUS SCHAAF P.S. 1 1/4" PIPE WITH CONC. TO BE MIDWAY AND ONLINE BETWEEN FND CORNER 1/2 MILE TO THE NORTH AND REESTABLISHED CORNER 1/2 MILE TO THE SO. N-S SMOOTH WIRE IS 2' WEST. CENTER N-S TRAIL ROAD IS 6' EAST.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

10

RESET SCHAAF MON. AND SET CARSONITE POST.

JACK PINE 7" N40°W 18.95'
JACK PINE 5" S38°W 23.78'
RED PINE 4" S02°W 35.96'
JACK PINE 4" N70°E 23.04'

E-10

RESET SCHAAF 1 1/4" PIPE MON. AND SET CARSONITE POST

JACK PINE 5" S50°E 31.32'
JACK PINE 14" N65°E 46.75'
JACK PINE 7" N45°W 39.29'
JACK PINE 9" S43°W 42.82'

Signed by Carl T Kiiskila
Surveyor's Michigan License No. 33981

Date 8-20-97

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

