

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in  
MONTCALM  
(County)

Located In:

Corner Code ≠

1. Public Land Survey

T 32N R 3E

K-9, L-9

T      R     

M-9

T      R     

T      R     

2. Property Controlling  
in Section

S 24 T      R     

16

S      T      R     

3. Miscellaneous  
Property in Sec.

S      T      R     

S      T      R     

Register of Deeds Stamp & File Number

4. Lot No.     , Recorded Plat     

5. Private Claims     

I, CARL KIISKILA, in a field survey on AUGUST 8, 19 96,  
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned  
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the  
current manual of survey instructions of the United States Department of the Interior, Bureau of Land  
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5  
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a  
Court of Law; established, re-established, monumented, re-monumented, recovered, found as  
expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded  
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

K-9

L-9

M-9

(NO EVIDENCE OF G.L.O. CORNER, B.T.'S, LINE TREES & TOPOGRAPHY,  
AS CALLED OUT IN THE G.L.O. LINE NOTES; UNLESS NOTED IN ITEM "B"  
BELOW.)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

K-9

L-9

M-9

16

REESTABLISHED THE SW COR  
S-24, 33' NORTH OF FENCE  
CORNER(FN E-W-S). CORNER FITS  
US GLO SWAMP TIES TO E &  
SOUTH; US=  
4 CHS (264') EAST TO CEDAR &  
ASPEN SWALE SE, WE MEAS  
271' +/-; US= 6.0 CHS (396')  
EAST TO LEAVE SWALE, WE MEAS  
384' AND US= 5 CHS (330')  
SOUTH TO ENTER CEDAR SWAMP E &  
W, WE MEAS 290' +/-.

FD PIPE FOR S1/4 COR S-24,  
PIPE FITS 2-PINE STUMPS PER  
RECORD US GLO (US = Y.PINE 18  
N35°E 17 LKS- 11.2'; Y.PINE 20  
S30°W 34 LKS- 22.4').  
N-S FENCE IS 4' WEST.

FD MI DEPT OF CONSERVATION MON  
AS SET BY KEN OSTLING IN 1966  
AT POSITION OF "FD OLD POST  
BOTTOM AT CORNER AS PRESCRIBED  
BY MN USDT, WHICH IS IN PLACE  
WITH EVIDENCE OF BOTH FACES".  
CTR OF POWER LINE OPENING IS  
310' +/- EAST.

ESTABLISHED THE SW COR OF THE  
SE1/4 OF THE SE1/4 OF S-24 PER  
STANDARD BLM INSTRUCTIONS.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-9

L-9

M-9

16

SET DNR MON.  
14" MAPLE S58°W 39.21'  
FN COR S09°W 33.0'  
14" OAK N77°E 30.03'  
12" OAK N29°E 46.93'  
6" OAK N07°W 61.84'

FD 1 1/4" x 24" IRON PIPE, SET  
1" x 32" IRON PIPE W/DNR ALUMN  
MON CAP & CEDAR POST.  
12" MAPLE S71°E 32.54'  
12" MAPLE S09°E 20.39'  
6" MAPLE N55°W 34.34'  
W.PINE N05°W 40.22'  
PINE STP USDT N39°E 11.1'  
PINE STP USDT N36°W 22.6'

FOUND DNR MON, SET CEDAR POST.  
110" OAK S68°W 28.43'  
110" OAK N04°W 29.60'  
8" OAK N22°E 33.66'  
7" OAK S11°W 6.31'  
-UPPER BLAZE & SIDE NAILS-  
3= OLD WITNESSES  
SW COR S-19, T32N-R4E FD DNR  
MON IS S01°39'06"E 326.99'

SET 5/8" x 32" REROD W/PS CAP &  
SET CARSONITE POST 1.5' NORTH.  
4" BALSAM S06°E 21.73'  
5" BALSAM S78°E 40.28'  
8" BALSAM N73°W 43.46'  
WHITE PINE N08°E 7.62'

60D SPIKE & BRASS TAGS & UPPER  
BLAZES.

Signed by

Carl T. Kiiskila

Date

2-27-97

Surveyor's Michigan License No.

33981