

LIBER 15528 PG 779

Jul 1995 129159

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

| | | |
|---------------------------|-------------|---------------|
| <u>Oakland</u> | Located In: | Corner Code # |
| (county) | | |
| 1. Public Land Survey | T1N R8E | K-9 |
| | T R | |
| | T R | |
| | T R | |
| 2. Property Controlling S | T R | |
| in Section S | T R | |
| 3. Miscellaneous S | T R | |
| Property in Sec. S | T R | |

\$ 7.00 MISCELLANEOUS RECORDING
 \$ 2.00 REMONUMENTATION
 19 JUL 95 2:05 P.M. RECEIPT# 71A
 PAID RECORDED - OAKLAND COUNTY
 LYNN D. ALLEN, CLERK/REGISTER OF DEEDS

Compliance with
 ACT 345, P.A. 1990

APPROVED ON: 7-12-95 TMS
 OAKLAND COUNTY REMONUMENTATION
 PEER GROUP COMMITTEE

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

I, Joseph C. Kapelczak, in a field survey on February 3, 1995, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, re-monumented, recovered, found as expressed below.

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Post set 1816 G.O.L. survey: N 62 W 31ls, 24" Ash; N 72 E 45ls, 8" Sugar.

No Land Corner Recordation Certificates Recorded

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Recovered 5/8" rerod in monument box at centerline of 10 Mile & Meadowbrook Rds.

Recovered witnesses:

N 52 E 79.48' Nail tag #28400(GLA) northwest side power pole
 S 38 E 82.58' Nail w/OCRC tag northeast side power pole
 S 47 W 73.96' Nail tag #28400 northwest side power pole
 N 43 W 73.95' Nail w/OCRC tag northeast side power pole
 N 65 E 66.90' 1/2" rerod cap #25829(JLB) corner parcel #22-24-351-027

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set 5/8" rerod with O.C. Remonumentation brass cap replacing 5/8" rerod

N 52 E 79.33' PK/remon tag northwest side power pole
 S 38 E 82.77' PK/remon tag northeast side power pole
 S 47 W 73.53' PK/remon tag northwest side power pole
 N 43 W 73.82' PK/remon tag southwest side power pole



Signed by

Joseph C. Kapelczak
 24598

Date

6/28/95

Surveyor's Michigan License No.

7.00
 2.00
 RM