

# SURVEY & REMONUMENTATION

MAY 22 1997

LIBER 16848 PG 780

Dec 18 96 305721

## COMMISSION

## LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Oakland  
(County)

Located in: Farmington Corner Code #  
Township

- |                                    |   |    |   |    |     |
|------------------------------------|---|----|---|----|-----|
| 1. Public Land Survey              | T | 1N | R | 9E | K-8 |
|                                    | T |    | R |    |     |
|                                    | T |    | R |    |     |
|                                    | T |    | R |    |     |
| 2. Property Controlling in Section | S |    | T |    | R   |
|                                    | S |    | T |    | R   |
| 3. Miscellaneous                   | S |    | T |    | R   |
| Property in Sec.                   | S |    | T |    | R   |

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_
5. Private Claims \_\_\_\_\_

\$ 7.00 MISCELLANEOUS RECORDING  
\$ 2.00 REMONUMENTATION  
18 DEC 96 1:37 P.M. RECEIPT# 35B  
PAID RECORDED - OAKLAND COUNTY  
LYNN D. ALLEN, CLERK/REGISTER OF DEEDS

Compliance with  
ACT 345, P.A. 1990

APPROVED ON: 10-23-96 TS  
OAKLAND COUNTY REMONUMENTATION  
PEER GROUP COMMITTEE  
Register of Deeds Stamp & File Number

I, Randy Kolehose, in a field survey on September 2 19 96, do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

**NOTE:** Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

### A. Description of original monument and accessories and/or subsequent restoration:

K-8	1817	Wampler	G.L.O.	Set Post
	1946	N/A	Sup. Middle Belt Ten Mile Road Plat No. 2 L. 58 P. 11	N/A
	1989	Milletics	Cert. Survey	N/A
	1993	Ward	L.C.R.C. L. 13584 P. 606	Boat Spike
	1995	Platz	L.C.R.C. L. 16037 P. 048	Boat Spike
	1995	Platz	Rec. Survey L. 16037 P. 636	Boat Spike

### B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

K-8 Found boat spike in a monument box on the C/L of Middle Belt Road running North and South 239' ± North of the C/L of Edgell Road running West per L.C.R.C. L. 13584 P. 606, L.C.R.C. L. 16037 P. 048, and Cert. Survey L. 16037 P. 636. This corner falls 1.17' North of the midpoint between K-7 and K-9. Checks distance North to K-7 per Milletics survey and South to K-9 per Supervisor's Middle Belt and Ten Mile Road Plat No. 2 L. 58 P. 11 (1946).

L.C.R.C. L. 13584 P. 606 (1993)

Due West 52.98' P.K. & Disc #22445 in S. face of utility pole  
N. 20° E. 193.17' P.K. & Disc #22445 in W. face of utility pole  
S. 05° E. 211.72' P.K. & Disc #22445 in E. face of anchor pole  
S. 35° W. 134.28' P.K. & Disc #22445 in S.E. face of 8" Maple

L.C.R.C. L. 16037 P. 048 (1995)

Due West 52.98'; P.K. & Disc #22445 in S. Face of Utility Pole  
N. 20° E. 193.17'; P.K. & Disc #22445 in W. Face of Utility Pole  
S. 05° E. 211.72'; P.K. & Disc #22445 in E. Face of Anchor Pole  
S. 35° W. 134.28'; P.K. & Disc #22445 in SE Face of 8" Maple

Measure North 2651.90' to K-7 (G.L.O. = 2640.0') (M&A = 2651.91') (PAE = 2651.92')

Measure South 2654.23' to K-9 (G.L.O. = 2640.0') (Sup. Middle Belt Ten Mile Road Plat No. 2 = 2654.6')

### C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-8 Replaced the boat spike with a 5/8" x 24" rebar with brass cap stamped "Oakland County Remonumentation P.S. #25854" in an existing monument box."

Set PK Nail & Tag Stamped "Oakland Co. Remonumentation P.S. #25854" in NW Side Util. Pole N 20° E 193.20'  
Set PK Nail & Tag Stamped "Oakland Co. Remonumentation P.S. #25854" in NE Side Guy Pole S 04° E 211.75'  
Set PK Nail & Tag Stamped "Oakland Co. Remonumentation P.S. #25854" in E Side 12" Maple S 34° W 134.33'  
Set PK Nail & Tag Stamped "Oakland Co. Remonumentation P.S. #25854" in S Side P. Pole N 80° W 53.22'

The selected location is accepted by the Contractor and is generally accepted by professional surveyors as the best available evidence of the position of the original corner.

Signed by Randy J. Kolehose Date 12/10/96  
Surveyor's Michigan License No. 25854

