## LAND CORNER RECORDATION CERTIFICATE

|   | LAND CORNER RECORDATION CI<br>Filing Requirement of Act 74, Mich.  | P.A. 1970  |         |
|---|--|--|---------|
| For corners in Oakland  | Located In: Corner Code #  | \$ 9.00 KISCELLANEOUS RECORDING  |         |
| (County)  | West Bloomfield Township   | \$ 2.00 REMONNMENTATION 30 NOV 98 8:36 A.M. RECEIPT# 25F   | A       |
|   | T2N R95 C-8  | PAID RECORDED - CAKLAND COUNT  | 1       |
| 1. Public Land Survey   | TR   | GLUTLLIAM CADRELL  |         |
|   | TR   | CLERK/REGISTER OF DEEDS  |         |
|   | TR   | Compliance with  |         |
| 2. Property Controlling   | S TRR.   | ACT 345, P.A. 1990<br>9-16-98 JS   |         |
| in Section 3. Miscellaneous   | S T R R 217AND   | APPROVED ON:   | fi      |
| Property in Sec.  | S T R  | i DEEK CHOOL COMMISSION  |         |
| r   | 25071/Ni   | Register of Deeds Stamp & File Nur   | iti     |
| 4 Lot No. Recor   | ded Plat <u>SECTION</u>  | ABCDEFGHIJK  | 1       |
| 5. Private Claims   |  | 1 1 1 1 1 1 1 1 1 1 1 1  | <b></b> |
|   |  |  |         |
|   | the colored an early state   | that under   | 1       |
| Huston K. Kennedy   | in a field survey on July 8, 1998 do hereby state in P.A. of 1970, the corner points mentioned in lines 1 and 2 a rules therefore as required in the current manual of survey instructions of a Court  | bave were in   |         |
| requirements of the contract  | therefore as required in the cultern manual of solve   | J Law and/of   | 1       |
| United States Department of the i   | rules therefore as required in the current manual of survey historics. Bureau of Land Management or by a decree of a Count of himes 3, 4 and 5 above were in conformance with the rules of a Decree of a Count of Law; established, re-established.  | the Michigan 6 19 19 19 19 19 19 19 19 19 19 19 19 19  |         |
|   |  | 1 - 4 do 1 31 - 1 - 22 - 1 - 22 - 1  | 2       |
| recovered, tourid as expressor as   | ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,  |  |         |
|   | ners, all in the same town and range, may be recorded  | 9 29 27 26   | 2       |
| NOTE: Not more trial 2 con on this certificate.   | 110.49   | 10-30-29-29  |         |
| •   |  | 31 32 34 35  | 3       |
| 1817-GLO Carpente<br>S54 1/2 E 46 1/3 Link<br>1.) 1975-Jones, PS<br>2.) 1990-Ward, PS<br>3.) 1991-Koh, PS # | #2934; LCRC L.0200, pg 01.111 - Fnd ½" Iron R<br>#22445; LCRC L.11211, pg. 111 - Fnd ½" Iron R<br>#26459; LCRC L.12149, pgs. 868 & 869 - Set ½   | od w/cap #21273<br>" Iron Rod w/cap #26459 as a reference corner   | to      |
| Which tails in the<br>4.) 1993-Milletics, f<br>5.) 1993-Milletics, f<br>Con'l on back si                    | >S #29249; LCRC L.13402, pg.643 — Fnd 1/2" from<br>>S #29249; LCRC L.13809, Pg.098 — Fnd capped<br>ide of LCRC   | rerod #21273, used same wit as 1993 LCRC   |         |
| 1998-Kennedy Sui  | evidence found and/or method applied in restoring or not be expensed in restoring or not be ex | eestablishing corner: Firon Rod capped #21273, 0.03 feet below the second representation of the found 1/2" from Ro   | od wi   |
| Militages from LC   | RC's #1, 2, 4 , 5 & Survey #8 were used to reco  | ver and veiny the location of the  |         |
|   |  |  |         |
| l accepted the four   | nd ½" Iron Rod w/cap #21273 as the best evidend  | e of the original corner positor.  |         |
| FIELD MEASURM   | ENTS BETWEEN   | ,  |         |
|   | •  | C-8 to C-8 GLO = 40 chains or 2640.00 Ft. Sidewell 18-19 (E ½ Sec 19) = 2782 200-0 Ft. Sidewell 18-19 (E ½ Sec 19) = 2782 200-0 Ft.  | Wes.    |
| <u>C-8 to C-7</u><br>GLO = 40 chains or   | 2640 00 Ft.  | GLO = 40 chains or 2640.00 Ft.<br>Sidewell 18-19 (E ½ Sec 19) = 2792 2765 21 (Sec 29) = 2792 2765 21 (Sec 29) = 2792 2765 21 (Sec 29) 2765 2765 2765 2765 2765 2765 2765 2765  | in the  |
| PRAZINI DEACH COI   | DNIKA CEOR ALTIONIC (TEETING   | Silvers tecotoen in France Lang. In MISLUM   | `₹      |
| Sidwell 18-19 (Sec  | 19) = 2617.88 Ft.<br>Liber 16288, Page 511 (Sec 19) = 2656.03 Ft.  | 2655.60 Pt. KENNEDY  | L) Ž    |
| Survey recorded in<br>2654.65 Ft. (GPS-I  | MEA)   |  | L 3 **  |
| ZOOMAN A (  | MEA) ument for corner and accessories established to perpet ound 1/4" from Rod wicap #21273 with a 4" diameter Co  | uate locating the position of the corners to the corners to the purpose with a ½" Iron Rookwith a 211663s cg   |         |
| <ul> <li>C. Description of monitors</li> <li>C.s.I rentaced the file</li> </ul>                             | ound 1/2" Iron Rod w/cap #21273 with a 4" diameter Co  | nuate locating the position of the committee a 21 602s concrete Monument with a 1/2" Iron Rock with a 21 602s concrete Monument with a 1/2" Iron Rock with a 21 602s concrete Monument with a 1/2" Iron Rock with a 21 602s concrete Monument with a 1/2" Iron Rock with a 21 602s concrete Monument with a 1/2" Iron Rock with a 21 602s concrete Monument with a 1/2" Iron Rock with a 21 602s concrete Monument with a 1/2" Iron Rock with a 21 602s concrete Monument with a 1/2" Iron Rock with a 21 602s concrete Monument with a 1/2" Iron Rock with a 21 602s concrete Monument with a 1/2" Iron Rock with a 21 602s concrete Monument with a 1/2" Iron Rock with a 21 602s concrete Monument with a 1/2" Iron Rock with a 21 602s concrete Monument with a 1/2" Iron Rock with a 21 602s concrete Monument with a 1/2" Iron Rock with a 21 602s concrete Monument with a 1/2" Iron Rock with a 1/2" Iro | JAN C.  |
| Caldand County Pot  | arionalite nous and a second   | "VI ESSIONA"   | ing are |
| N86°W 30.49° NE   | Corner of House III  | رسوم باهات کا کام باهاده .   |         |
| N53°F 25.8/15et i   | Viag Ivali & Ivalitation   |  |         |
| \$84°E 7.85' Set M  | hamanna steamant to the part of the grant to   | y Professional Surveyors as the best available e   | viden   |
| The selected location   | n is accepted by me and is generally accepted to   | · · · · · ·  |         |
| the position of the p   | iginal comer.  | Date 10-9-96   |         |
| · \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \   | wf 6. to   | Date   |         |
| Signed by: Surveyor's Michighan   | inansa No. 17623   | ED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYOR'S  | JAN.    |
| Surveyors Michigham   | MODEL ADDROVE  | id by Michigan State Board of Professional Solve i City  |         |