

LIBER 19548 PG 787

For corners in

Oakland

(County)

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

Located in:

West Bloomfield Township

Corner Code #

1. Public Land Survey

T2N R9E D-13

T R

T R

T R

T R

2. Property Controlling  
in Section

S T R

S T R

3. Miscellaneous  
Property in Sec.

S T R

S T R

SECTION

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_

5. Private Claims \_\_\_\_\_

\$ 7.00 MISCELLANEOUS RECORDING

\$ 2.00 REMONUMENTATION

11 FEB 99 9:02 A.M.

RECEIPT# 3

PAID

RECORDED - OAKLAND COM

G. WILLIAM CADDELL

CLERK/REGISTER OF DEEDS

Compliance with  
ACT 345, P.A. 1990APPROVED ON: 2-3-99 JS  
OAKLAND COUNTY REMONUMENTATION  
OFFER GROUP COMMITTEE

Register of Deeds Stamp &amp; File No.

I, Huston K. Kennedy, in a field survey on October 27, 1998 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

- A. Description of original monument and accessories and/or subsequent restoration:  
1817-GLO Carpenter, D.S.; Set Post 9" Red Oak S30 1/4°E 80 Links; 18" White Oak N27 2/3°W 50 Links  
1.) 1994-Wozniak, PS #15086; LCRC L.14709, Pg.321 - Set a PK Nail  
2.) 1997-Ward, PS #22445; LCRC L.174, Pg.863 (D-1 for Farmington Twp.) - Fnd a PK Nail  
3.) 1962-Oakland County Road Commission Unrecorded Witnesses - Object found not stated

- B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:  
1998-Kennedy Surveying, Inc. - Kennedy, PS #17623 - Fnd a 1/2" Iron Rod w/2" diameter brass cap stamped Oakland County Remonumentation, PS #22445 in a existing Monument Box located 3 feet North of the existing centerline of 14 N Road extending to the East & West, which has a bituminous surface, an old fence-tree row extending to the North. This c is being accepted and used as a common corner with the North 1/4 corner of Section 5, T1N, R9E, Farmington Township

Witnesses from LCRC #1 & 2 were used to recover and verify the location of the found 1/2" Iron Rod w/2" diameter brass stamped Oakland County Remonumentation, PS #22445 in a existing Monument Box

I accepted the found found 1/2" Iron Rod w/2" diameter brass cap stamped Oakland County Remonumentation, PS #2244 existing Monument Box as the best evidence of the original corner position.

## FIELD MEASUREMENTS BETWEEN

## D-13 to C-13

GLO = 40 chains or 2640.00 Ft.

"THE GLENN'S OF CHELSEA PARK (Sec 32) = 2647.88 Ft.  
2643.96 Ft. (GPS-MEA)

## D-13 to E-13

GLO = 40 chains or 2640.00 Ft.

No plat or sidwell distances  
2645.75 Ft. (GPS-MEA)

- C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:  
D-13 I accepted the found 1/2" Iron Rod w/2" diameter brass cap stamped Oakland County Remonumentation, PS #2244 existing Monument Box  
S05°W 39.36' Fnd Mag Nail & Remon Washer #22445 West face 31" Elm  
N10°W 32.06' Cut "x" on top of bolt for Fire Hydrant  
S62°E 106.48' Cut "x" on top of bolt for Fire Hydrant  
S48°W 138.40' Set Mag Nail & Remon Washer NW face Guide Pole  
North 60.06 feet found 4" diameter Concrete Monument

The selected location is accepted by me and is generally accepted by Professional Surveyors as the best available evidence of the position of the original corner.

Signed by: \_\_\_\_\_

Surveyor's Michigan License No. \_\_\_\_\_

Date

2-5-99

