HRFR 19489PG259 Filing Requirement of Act 74, Mich. P.A. 1970

For corners in Oakland (County)	Located In: Corner Code # West Bloomfield Township		
1. Public Land Survey	T <u>2N</u> T T	R9E R R	E-10
Property Controlling in Section Miscellaneous Property in Sec.	ST ST ST	R R R R	
4. Lot No, Record 5. Private Claims	ed Plat		SECTION

I, Huston K. Kennedy. In a field survey on August 10. 1998 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan that the corner points mentioned in lines 1 and 2 above were in the conformance of a Court of Law; established, re-established, monumented, recovered, found as expressed below: recovered, found as expressed below:


NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

2 \$ 7.00 MISCELLANEOUS RECORDING \$ 2.00 REKONNENTATION RECEIPTH BOA 27 JAN 99 9:28 A.M. RECORDED - CARLAND COUNTY PAID G.WILLIAM CADDELL CLERK/REGISTER OF DEEDS

> Compliance with ACT 345, P.A. 1990

1-13-99 73 APPROVED ON: OAKLAND COUNTY REMONUMENTATION PEER GROUP COMMITTEE

Register of Deeds Stamp & File Numb



- Description of original monument and accessories and/or subsequent restoration: 1817-GLO Carpenter, D.S.; Set Post 7" Red Budd S80 1/2"W 21 1/2 Links; 9" Hickory N75 1/2"E 35 1/2 Links
 - 1.) 1962-Oakland County Road Commission unrecorded witnesses Object found not stated
 - 1962-Oakland County Road Commission unrecorded witnesses Fnd 1" Iron Pipe
 - 1966-Oakland County Road Commission unrecorded witnesses Fnd 1" Iron Pipe
- Description of corner evidence found and/or method applied in restoring or reestablishing corner:
 998-Kennedy Surveying, Inc. Kennedy, PS #17623 Fnd a ½" Iron Rod in a Monument Box located in the existing centerline of Drake Road extending to the North & South, which has a bituminous surface, 30 feet South of the existing centerline of Brookstone Court extending to the East, which has a bituminous surface. A old fence row extends to the East &

Witnesses from Oakland County Road Commission unrecorded witnesses #1, 2 were used to recover and verify the localic West. of the found 1/2" Iron Rod in a Monument Box. HUSTON KENNEDY PROFESOR

I accepted the found 1/2" Iron Rod in a Monument Box as the best evidence of the original comer positon.

FIELD MEASURMENTS BETWEEN

Surveyor's Michignan License No.

E-10 to E-9 GLO = 40 chains or 2640.00 Ft. Sidwell (W 1/2 of N 1/2 of Sec 28) = 2645.55 Ft. Sidwell (E 1/2 of Sec 29) = 2643.71 Ft.

E-10 to E-11 GLO = 40 chains or 2640.00 Ft. No plat or sidwell distances 2646.14 Ft (GPS-MEA)

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner E-10 I replaced the found 1/2" Iron Rod with a 5/8" × 24" Iron Rod 17023 Description of monument for corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the position of the corner and accessories established to perpetuate locating the perpetuate locating the perpetuate locating the perpetuate locating the perpetuate location and accessories established to perpe N65°W 52.91' Cut "x" on top of bolt on Fire Hydrant S41°W 77.23' Set Mag Nail & Remon Washer SE face 30" Oak N46°E 118.66' Set Mag Nail & Remon Washer NW face 10" Ash N79°E 53.54' Set Mag Nail & Remon Washer North face 8" Oak

N79°E 53.54' Set Mag Nail & Remon Washer North 1400 0	Destancional Surveyors as the best available evidence (
N79°E 53.54' Set Mag Nail & Remon Washer North table 18 North tabl	Projessional deliverage as
the position of the original corner. Signed by	Date 1-15-99
Signed by 17/72	