

COPY

LIBER 18604 PG 259

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Oakland
(County)

Located In: Corner Code #
West Bloomfield Township

1. Public Land Survey

T2N R9E K-4

2. Property Controlling
in Section

S T R
S T R
S T R
S T R
SURVEY 2
SECTION
MAR 21 2000

3. Miscellaneous
Property in Sec.

4. Lot No. Recorded Plat

SECTION

5. Private Claims

\$ 7.00 MISCELLANEOUS RECORDING
\$ 2.00 REMONUMENTATION
18 JUN 98 8:17 A.M. RECEIPT# 404
PAID RECORDED - OAKLAND COUNTY
LYNN D. ALLEN, CLERK/REGISTER OF DEEDS

Compliance with
ACT 345, P.A. 1990

APPROVED ON: 4/21/98 JS
OAKLAND COUNTY REMONUMENTATION
PEER GROUP COMMITTEE

Register of Deeds Stamp & File Number

I, Huston K. Kennedy, in a field survey on April 6, 1998, I hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:
1817-GLO Carpenter, D.S.; Set Post 10" Red Oak S02°E 11 1/4° Links; 12" Red Oak S87°W 35 Links

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:
1998-Kennedy Surveying, Inc. - Kennedy, PS #17623 - The corner has not been perpetuated.

HOW THE CORNER WAS RECOVERED

I did not receive any information regarding this corner from other sources and the corner is not tied to a recorded plat. recovered the corner at the midpoint on a straight line between K-3 and K-5.

FIELD MEASUREMENTS BETWEEN

K-4 to K-3

GLO = 40 chains or 2640.00 Ft.
No plat or sidwell distances
2663.25 Ft. (GPS-MEA)

K-4 to K-5

GLO = 40 chains or 2640.00 Ft.
No plat or sidwell distances
2663.25 Ft. (GPS-MEA)

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
K-4 I set a 5/8" x 24" Iron Rod with 2" diameter brass cap stamped Oakland County Remonumentation PS #17623
N52°E 61.61' SW corner of tennis building
N17°W 70.73' NW corner of tennis building
S32°E 17.20' NE corner of building
S07°E 54.98' NW corner of building

The selected location is accepted by me and is generally accepted by Professional Surveyors as the best available evidence of the position of the original corner.

Signed by: [Signature]

Surveyor's Michigan License No. 17623

Date 4-24-98

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1991
REVISED MAY 14, 1991
REVISED JAN., 1991
REVISED OCT., 1991

