

LIBER 19350PG866

## LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Oakland

(County)

Located in:

West Bloomfield Township

Corner Code #

1. Public Land Survey

T2N R9E M-9

2. Property Controlling  
in SectionS T R  
S T R  
S T R  
S T R3. Miscellaneous  
Property in Sec.

SECTION

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_  
5. Private Claims \_\_\_\_\_

I, Huston K. Kennedy, in a field survey on September 15, 1998 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, recovered, found as expressed below:

**NOTE:** Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:  
1817-GLO Carpenter, D.S.; Set Post 11" Black Oak N49°W 8 Links

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:  
1998-Kennedy Surveying, Inc. - Kennedy, PS #17623 - Fnd a 4" diameter Concrete Monument with a 2" diameter brass cap stamped Oakland County Remonumentation #24598 located 34 feet West of the existing centerline of Inkster Road extending to the North & South, which has a bituminous surface, and in the existing centerline of Quarton Road extending to the East, which has a bituminous surface. This corner is being used and accepted as a common corner with Sections 19 & 30, T2N, R10E, Bloomfield Township (A-9).

## FIELD MEASUREMENTS BETWEEN

## M-9 to M-8

GLO = 40 chains or 2640.00 Ft.

No plats or sidwells distances

Survey recorded in Liber 8898, Pg. 796 = 2731.02 Ft. + 6.77 Ft. = 2737.79 Ft.

2736.34 Ft. (GPS-MEA)

## M-9 to M-10

GLO = 40 chains or 2640.00 Ft.

"HERNDON'S WALNUT LAKE ESTATES" + "HERDON'S WALNUT LAKE ESTATES NO.1" + "SUPERVISOR'S PROFESSIONAL SURVEYOR 17623"

FARMS" (Sec 25) = 2508.64 Ft.

2508.17 Ft. (GPS-MEA)

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:  
M-9 I accepted the found 4" diameter Concrete Monument w/2" diameter brass cap stamped Oakland County Remonumentation, PS #24598  
S43°W 49.72' Fnd Mag Nail & Remon Washer stamped Oakland County Remon. PS #24598 SE face 26" Maple  
S41°E 88.30' Fnd Mag Nail & Remon Washer stamped Oakland County Remon. PS #24598 NE face Power Pole  
N03°W 58.71' Fnd Mag Nail & Remon Washer stamped Oakland County Remon. PS #24598 West face 11" Cedar  
Due East 8.06' cut "x" on North rim of Sanitary Manhole

The selected location is accepted by me and is generally accepted by Professional Surveyors as the best available evidence of the position of the original corner.

Signed by:

Date

12-5-98

Surveyor's Michigan License No.

17623

\$ 7.00 MISCELLANEOUS RECORDING

\$ 2.00 REMONUMENTATION

5 JAN 99 8:23 A.M. RECEIPT# 7A

PAID RECORDED - OAKLAND COUNTY

G. WILLIAM CADDELL

CLERK/REGISTER OF DEEDS

Compliance with  
ACT 345, P.A. 1990APPROVED ON: 12-01-98 SS  
OAKLAND COUNTY REMONUMENTATION  
PEER GROUP COMMITTEE

Register of Deeds Stamp &amp; File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

700 FILE  
200