

UNER 19681 PG 735

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in	,, , ,		85136
Oakland (County)	Located In: Corner Code West Bloomfield Township	\$7.00 H \$2.00 R	19681 PAGE 735 ISC RECORDING EMONUMENTATION
1. Public Land Survey	T <u>2N</u> R <u>9E M-1</u> T R —	3 03/16/1 PATD	993 08:26:39 A.H. RECEIPT# 7653 RECORDED - OAKLAND COUNTY IAM CADDELL. CLERK/REGISTER OF DEEDS
Property Controlling in Section Miscellaneous Property in Sec.	S_ T_ R	·	Complicate with ACT 345. P.A. 1998 ROVED ON: 3-3-54 LAND COUNTY REMONUMENTATION PEER GROUP COMMITTEE Indicates of Deeds Stamp & File Number
4. Lot No, Reco	rded PlatSEC	10N 1 2 6-3	C D E F G H I J K L M
requirements of P.A. 74, twicingal conformance with regulations and United States Department of the that the corner points mentioned is Board of Land Surveyors or by recovered, found as expressed be	in a field survey on February 15., 1999 of n.P.A. of 1970, the corner points mentioned in lin rules therefore as required in the current manual metror, Bureau of Land Management or by a decrent lines 3, 4 and 5 above were in conformance with a Decree of a Court of Law; established, reslow: Theres, all in the same town and range, may be	of survey instructions of the se of a Court of Law and/or h the rules of the Michigan established, monumented,	
1817-GLO Carpente 1.) 1997-Ward, PS #	monument and accessories and/or subsector, D.S.; Set a post K22445; LCRC for (M-1 Farmington Tv	wp.) L17486, pg.797 — Fnd as	
stamped Oakland C This corner has bee Bloomfield Township	p (A-13), the Northwest corner of Sec TAN POE Estimation Township (M-	at the base of a hill and 50 feet orner with the Southwest corner tion 6, T1N, R10E, Southfield T 1)	r of Section 31, 1214, 14162., Township (A-1) and the Northeast
			and verify the location of the found 4" numeritation, PS #22445.
	ound found 4" diameter Concrete PS #22445 as the best evidence of	Monument w/2" diameter b	rass cap stamped Calada.
FIELD MEASURME			A MANAGER AND A STATE OF MANAGEMENT REPORTED TO
M-13 to M-12 GLO = 40 chains or 2	2640.00 Ft.	M-13 to L-13 GLO = 40 chains or 2640.00 No plat or sidwell distances	Ft. HUSTON

GLO = 40 chains or 2640.00 Ft.

"MEADOWLAKE FARMS NO. 1" = 2661.81 Ft. (CAL)

2661.96 Ft. (GPS-MEA)

C. Description of monument for corner and accessories established to perpetuate locating the position of the carrier of the carrie

The selected location is accepted by me and is generally accepted by Professional Surveyors as the best available evidence of the position of the original corner.

the position of the original corner.	- 2
the position of the original corner. Signed by: 017623 Surveyor's Michignan License No. 017623	Date 3-5-99
Signed by: 1747.3	
Surveyor's Michignan License No.	FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYOR'S
	FORM VELLOADD DI MICHIGANIA