SURVEY & REMONUMENTATION

MAR 04 1998

tiber 17156 % 280

S	F	Ci	()	N
3.0	_	U	w	N

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74 Mich. P. A. 1979

For corners in		uirement of Act 74, N		\$ 9.00 HTSC	ELLANEOUS RECO	מערמס
Oakland	Located in: Troy Twp. C	Corner Code #		\$ 2.00 REMO	WHENTATION	Chitch
(County)				24 APR 97 8	49 A.M. R	ECEIPT# 354
1. Public Land Survey	T_2M R_11E TR TR	B-11			RECORDED - CA N. CLERK/REGIS	KLAND COUNTY TER OF DEEMS
	Ť <u> </u>					
2. Property Controlling	S TR				3-25-57	
in Section 3. Miscellaneous	S TR S TR			AKLAND COL		155
Property in Sec.	S TR	· · · · · · · · · · · · · · · · · · ·		PERKE	RO COST	
,	·—···			Register of I	Deeds Stamp &	File Number
4 Lot No Door-	d= 2 m(=1					•
4. Lot No, Records. Private Claims	ued Plat		_	ABCD	EFGH	IJKL
			1 2			
			3	lilĭ	1 1	-2- -1-
Huston K. Kennedy	in a field survey on2/	24, 1997 do hereby st	ate that under	78-		11 12
requirements of P.A. 74, Michigal conformance with regulations and	R M.A. Of 1970. The corner points	mentioned in lines 1 and 2.	ahova umra in			
United States Department of the Ir	nterior, Bureau of Land Manageme	ent or by a decree of a Court	of law and for		16 15	
that the corner points mentioned in Board of Land Surveyors or by	in lines 3, 4 and 5 above were in c	Onformance with the rules of	the Michigan			1 1
recovered, found as expressed bei	ow:	stabilisticu, re-estabilisticu,	monumentea, 8	1920-	21 22	
NOTE: Not more than 2 corn	ers, all in the same town and ra	nge may be recorded	9			
on this certificate.		ngo, may be recorded	10	3029	28 27	
			11	-		
			12	31	33 34	3536
A. Description of original mor			13			
3.) 1924-"EAST MAPLE GARDI B Description of corner evide		plied in restoring or second	abliah in a sasasas			
1997 Kennedy Surveying, In side of a railroad ov	c Kennedy, PS #17623 - 1 erpass crossing Maple Road	Fnd 1/2" Iron Pipe set extending to the East	a 1' diameter cl & West, which h	as a bitumino	ous surface.	
Witnesses from LCRC #1 of the found 1/2" Iro	l, Unrecorded Survey and "EA n Pipe set a 1' diameter c	ST MAPLE GARDEN", L.31 lay pipe filled with c	, Pg.15 of OCR we oncrete.	re used to re	cover and verif	y the location
I accepted the found in position.	l/2" Iron Pipe set a 1' diam	meter clay pipe filled	with concrete as	the best evi		
m2.13					90))
	tween see back side of LCRO				4	V
C. Description of monument for						
S36°E 87.09' Set PK & N35°W 77.09' Set PK & N47°R 46.80' Set PK &	Remon Washer SE corner of Remon Washer SW corner of Remon Washer NE corner of Remon Washer NE corner of	bridge corner bridge corner bridge corner	ssing maple Road			
The selected location is a position of the original co	coantad hu ma and !		• -		Marinin	Hillippe.
position of the original co	proposed by me and is generally ener.	ally accepted by Profe	ssional Surveyor	s as the bes	A STATE OF	dente of the
	- I			į	HUSTO	ON X F
Signed by	<i>X</i>		2-20	. o7	KENNE	IONAL 英星
Surveyor's Michigan License No	170 72		Date 2 2	<u> </u>	SURVE	ON SON THE CONTROL OF
Surveyor a Milchigant License NC		· · · · · · · · · · · · · · · · · · ·		7	1762	SUPPLEMENT OF THE STREET
					PROFFEEIN	MAI SUPPLIE
		FORM APPRO	VED BY MICHIGAN STA	TE BOARD OF PRO	"" REVE	PS WHR. 28, 1971 SED MAY 14,1975
						EVISED JAN., 1983 EVISED OCT., 1995

Ä.

SURVEY & REMONUMENTATION

MAR 0 4 1998

UBER 1715 6 1 281

SECTION

FIELD MEASUREMENTS BETWEEN

B-11 to A-11

GLO = 40.30 chains or 2659.80 Ft.
"BIRNINGHAM ESTATES" = 2676.30 Ft.
"BIRNINGHAM ESTATES" + "BIRNINGHAM GARDENS" = 2675.10 Ft
GPS-NEA = 2674.60 Ft.

B-11 to C-11

GIO = 40 chains or 2640.00 Ft. "EAST MAPLE GARDENS" = 2603.50 Ft. GPS-MEA = 2593.90 Ft.