

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

OAKLAND

(County)

PONTIACLocated In: TWP. Corner Code # D-9

206156

LIBER 20101 PAGE 716
 \$7.00 MISC RECORDING
 \$2.00 REMONUMENTATION
 06/10/1999 12:32:43 P.M. RECEIPT# 4
 PAID RECORDED - OAKLAND COUNTY
 G. WILLIAM CADDELL, CLERK/REGISTER O
 Compliance with
 ACT 345, P.A. 1990

APPROVED ON: 4-27-99 JS
 OAKLAND COUNTY REMONUMENTATION
 PEER GROUP COMMITTEE

Register of Deeds Stamp & File Num

1. Public Land Survey

T 3NR 10E D-9T RT RT R

2. Property Controlling in Section

S TT RS TT R

3. Miscellaneous Property in Sec.

S TT RS TT RSURVEY &
REMONUMENTATION

MAR 21 2000

SECTION

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

RAYMOND J. McCOY

April 23 99

I, _____, in a field survey on _____, 19____ do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

WAMPLER, D.S., SET POST
 THERE ARE NO LCRC'S RECORDED.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

No corner was found. Corner was established by using found monumentation in "FOSTER AND TREGENTS ADDITION"(L. 4, Pg. 8, 1867), more particularly monuments and iron pipes along the Right-Of-Way of Bladwin Ave. with the found monument at Howard & Foster St.

State Plane Coordinate N 420200.0339
E 13410506.8258

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set a 5/8"x24" iron rod with a 2" diameter brass disk stamped Oakland County Remonumentation P.S. #21270 in a New Monument Box.

Witnesses:

N 14° W, 88.96, Set OCRT #21270 in East face of Power Pole

N 16° E, centerline, SW bolt of Light Pole Base

N 61° E, 37.01, Northwest corner Block Bldg. #118 Bladwin

S 60° W, 19.54, Set OCRT #21270 in NW face of Power Pole

THE SELECTED LOCATION IS ACCEPTED BY ME AND IS GENERALLY ACCEPTED BY
 PROFESSIONAL SURVEYORS AS THE BEST AVIALABLE EVIDENCE OF THE POSITION OF THE
 ORIGINAL CORNER.

Signed by

Surveyor's Michigan License No. 21270Date May 28, 1999