

SURVEY &
REMONUMENTATION

OCT 27 1993

COMMISSION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

STATE OF MICHIGAN
COUNTY OF OCEANA
RECEIVED FOR RECORD

100504

'93 OCT -7 P2:45

For corners in
OCEANA

(County)

Located In:

Corner Code =#

1. Public Land Survey

T 15N R 17W

F-7

T R

T R

T R

T R

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous
Property in Sec.

S T R

S T R

4. Lot No. , Recorded Plat

5. Private Claims

Jeff E. Martin
REGISTER OF DEEDS

Register of Deeds Stamp & File Number

J. Randolph Hepworth

September 27, 1993

I, _____, in a field survey on _____, 19_____, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

A. F-7 1/4 CORNER COMMON TO SEC 16 & 21 HART TWP T15N, R17W
GLO SET POST 12" BEECH N24°E 16.5' 10" BEECH S49°E 7.3'
OCRC WITNESS BOOK: 4-10-51 PD 1" IRON
16" BLK S45°E 53.3
8" MAPLE N50°E 55.8'
PPOLE S45°W 79.55
TEL MARKER S45°E 52.80

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner

FOUND R/R SPIKE AND IS ACCEPTED AS A CAREFUL AND FAITHFUL PERPETUATION OF THE POSITION OF THE ORIGINAL CORNER.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner.

F-7 1/4 COR. COMMON TO 16 & 21; T15N, R17W
SET "COUNTY SURVEYOR" HARRISON 4"x20" CAST IRON MONUMENT IN PLACE OF FOUND R/R SPIKE

T ROAD INTERSECTION E - W & S			
60d SPK SW FACE	TEL. POLE	S70°E	124.60
60d SPK NW FACE	POWER POLE	S25°W	85.89
CENTER	STOP SIGN	S30°E	48.34
60d SPK NW FACE	POWER POLE	S75°W	78.94
CENTER	STREET SIGN POST	N15°E	22.96



Signed by

Date

September 30, 1993

Surveyor's Michigan License No.

26457

11-5-93