SURVEY & REMONUMENTATION

JAN 1 1 1999

SECTION

For corners in

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

100835
STATE OF MICHIGAN
COUNTY OF OCEANA
RECEIVED FOR RECORD

28 DEC 1998 4:28:43 PM

Oceana	1	Corner Coo	do#			JOSEPH E, ME	
(County)	Located In:				1	REGISTER OF	DEEDS
1. Public Land Survey	T I	R17W G-	8				
Property Controlling in Section Miscellaneous Property in Sec.	S TI S TI S TI	\frac{\}{\}_{\}_{\}_{\}_{\}_{\}_{\}_{\}_{\}_{			Register of [)eeds Stamp	& File Number
4. Lot No, Reco	orded Plat				A B C D	E F G H	I J K L
J. Randolph Hepwork, requirements of P.A. 74, Michiconformance with regulations at United States Department of the that the corner points mention Board of Land Surveyors or recovered, found as expressed	igan P.A. of 1970, the or igan P.A. of 1970, the or ind rules therefore as reque e Interior, Bureau of Land ed in lines 3, 4 and 5 abo by a Decree of a Cour	orner points mentioned in the current mad Management or by a live were in conformant.	d in lines 1 a nual of surve decree of a ce with the re	Court of Law and /or ules of the Michigan	2 6 5 3 4 7 8 5 5 6 19 17 7 8 8 19 20 20	9-1-16-11	5 14 13
NOTE: Not more than 2 or on this certificate.		own and range, may	i be recorde	ed	9 10 30 29 11 12 31 32 13	28——2 ——33——3	72625- 43536-
GLO SET POST 10" Book A, Pg 12; S. Edson, Book A, Pg 130; S. Edsor Unrecorded Survey, R. H 8" Cherry Clp 6" Majple Fd 1/2" Iron by Hepworth 60d Spk 60d Spk 80d Spk N	OMMON TO SECTIONS Beech N88°E 28' 1879; No information n, 1882; "A tyle the dis epworth # 26457, OCR 74°AZ 91.33' 153°AZ 75.10'	S 21 AND 22, T15N, 10" Lynn N51°V given ameter of which is ab C Witnessing, 5-27-8: 8" Maple 122 Clp 6" Maple 20 en 7-29-93 le 300°AZ 70°AZ Haple 205°AZ Maple 205°AZ	, R17W HA V 25' out six inche	es." ' X 2' iron i4' Tape Tape Tape	Oceana Count Peer Group Ro Date:	eviewed & Ap 20-13-98 epworth	pproved
B. Description of con I found a JRH 1/2" Iron ir established by me in May corner very good. I accept the 1/2" Iron as believe that the corner si C. Description of may Set 4"x20" Harrison Cas 60d Spk NE Face 60d Spk SW Face 60d Spk NE Face	n the centerline intersectly, 1989 using the local of a careful and faithful rehould be at another local onument for corner at Iron Monument, stamp Power Pole Guy Pole 10' Maple	tion of gravel roads Not collateral evidence of establishment of the and accessories end "County Surveyor 300°AZ 70°AZ 120°AZ	t-E&SW. No the road ce position of the costablished	to occupation is visib nterlines. Measure the original corner.	ole to the west or sou ement north to the 1/ No evidence is know ecating the position	oth. This com the line fence a win to me that we the com the com	would lead me to
60d Spk N Face 60d Spk NW Face 60d spk E Face	Cip 6"-10" Maple Tw 8" Maple 8" Maple	205°AZ 155°AZ 192°az	75.02' 67.13	EDM EDM			NDOLPH *

puntl

26457

Signed by _

Surveyor's Michigan License No.

November 10, 1998

Surveyor No.