

SURVEY & REMONUMENTATION

APR 29 1995

COMMISSION LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Ogemaw

(County)

Located in:

Corner Code #

1. Public Land Survey

T21NR 1E

M-9

2. Property Controlling in Section

S

T

R

3. Miscellaneous Property in Sec.

S

T

R

S

T

R

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

LIBER 3 PAGE 22

STATE OF MICHIGAN
OGEMAW COUNTY
RECORDED

28 DEC 95 3:20 P.M.

WANDA HUZIK
REGISTER OF DEEDS

Register of Deeds Stamp & File Number

I, Timothy L. Lapham, in a field survey on December, 1995 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and for that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

M-9: GLO Clason 1838, Set Post, 6" Cedar S43W 7 lns, 10" Cedar N67W 8 lns; 2/22/1993 Survey, Lapham, not recorded, spike, 3 witnesses 1995 DNR survey, Roser, not yet completed, accepted existing spike for corner.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

M-9: No evidence of GLO survey found. Found DNR capped iron at intersection of dirt roads East-West-North. Matches Lapham survey. Accepted found iron as best evidence of the position of the corner. See dossier for additional information.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

M-9: Set 5/8" X 36" rerod with 3-1/4" Aluminum Ogemaw Remon capp Marked "27595 1995"
From Which:
N58E 69.77' Power pole w/spike
S58W 34.72' Telephone pedestal
S82W 74.18' 10" Ash with spike
N32W 79.35' 10" Poplar w/spike

APPROVED BY
PEER REVIEW

12/20/95

DATE

P.A. 345 of 1990

Signed by _____
Surveyor's Michigan License No. 27595

Date

12/28/95