

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:
Ogemaw
(County)

Located In

Corner Code #

1. Public Land Survey

T 21N R 2E L-3
T 21N R 2E K-3

2. Property Controlling
in Section

S T R
S T R

3. Miscellaneous
Property in Section

S T R
S T R

4. Lot No:

Recorded Plat:

5. Private Claims:

I, Carl T. Kiiskila, in a field survey on July 16, 2007 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

L-3 G.L.O. 1846 B.F. Hall Set quarter section post.

Wit: W. Pine 18 N30°E 13 links

W. Pine 20 S24°E 11 links

1968 Consumers Power Co. Set "T" iron midway and online

Wit: 18" Norway NW 40.10'

38" W. Pine North 36.0'

6" J. Pine ENE 59.9'

8" Twin Maple SW 37.7'

K-3 G.L.O. 1846 B.F. Hall Set Post corner sections 1,2,11&12.

Wit: W. Pine 18 S83°E 26 links

W. Pine 16 N75°E 25 links

1968 Consumers Power Co. Set "T" iron for the corner while working in section 1.

1988 Liber 2, Page 18, T. Lapham P.S.# 27595 Fd. "T" iron

Wit: 10" Oak N10°W 10.10'

10" Oak N60°W 44.82'

8" Oak S30°E 21.96'

Ctr 2 track East 20'

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

L-3 Found "T" iron fitting Consumers Power Co. survey in section 1.

K-3 Found bent "T" iron fitting Consumers Power Co. survey and T. Lapham's witnesses.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

L-3 Set Standard DNR monument

Wit: Set nail and tag W. side of a 26" R. Pine N35°W 40.62'

Set nail and tag S. side of a Triple Maple S49°W 35.82'

Set nail and tag W. side of a 6" Maple S20°E 45.83'

Set nail and tag S. side of a 6" Oak N70°E 45.83'

Face blaze on 30" dead White Pine N1°E 50.9'

K-3 Set Standard DNR monument over found "T" iron

Wit: Set nail and tag N. Side of a 16" R. Oak N78°W 45.27'

Set nail and tag S.W. side of a 11" Oak S33°E 21.76'

Set nail and tag E. side of a 16" Red Oak N14°W 10.54'

Set nail and tag N. side of a 14" Maple S75°E 27.71'

Signed by:

Carl T. Kiiskila

Date:

12/19/07

Surveyor's Michigan License No.:

33981

