

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:
Ogemaw
(County)

Located In

Corner Code #

1. Public Land Survey T 21N R 2E K-2
T
2. Property Controlling in Section S T R
S T R
3. Miscellaneous Property in Section S T R
S T R

Register of Deeds Stamp & File Number

4. Lot No: Recorded Plat:

5. Private Claims:

I, Carl T. Kiiskila, in a field survey on July 16, 2007 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

A. Description of original monument and accessories and/or subsequent restoration:
K-2 G.L.O. 1846 May 14, B.F. Hall used a Hemlock 12" for the quarter section post

1970 James E. Richardson R.L.S.#2527 set 1/2" rod prorated from the section corner 1/2 mile to the south and an old fence corner 1/4 mile to the north. Wits: W. Oak 16" N35°E 38.08', W. Oak 6" N44°W 61.66', R. Oak 16" S24°W 49.35', R. Oak 14" S13°E 45.87'

Liber 1, page 238 Jerry L. Wilcox P.S. #14102 found a 5/8" iron for corner. Wit: 4" Oak S20°W 60.28', 22" Oak N39°E 38.12', 22" Oak N06°E 56.63',

10" Twin Maple N51°W 65.40'

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

K-2 Found P.K. nail fitting J.L. Wilcox's witnesses and J.E. Richardson's survey in section 2.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-2 Set 5/8" X 32" iron rod with P.S. Cap #33981
Wit: Set nail and tag Northeast side of a 14" Oak N37°W 61.75'
Set nail and tag West side of a 20" Oak N11°E 56.96'
Set nail and tag Southeast side of a 6" Oak S26°W 60.25'
Set nail and tag Northeast side of a 8" R. Maple S20°E 66.94'



Signed by:

Carl T. Kiiskila

Date:

12/19/07

Surveyor's Michigan License No.:

33981