

# LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:

OGEMAW

(County)

Located In

Corner Code #

1. Public Land Survey	T	21N	R	3E	C-3
	T	21N	R	3E	C-4
2. Property Controlling in Section	S	T	R		
	S	T	R		
3. Miscellaneous Property in Section	S	T	R		
	S	T	R		

4. Lot No: Recorded Plat:

5. Private Claims:

I, Carl T. Kiiskila, in a field survey on June 16, 2009 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

**NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.**

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6	5		4		3		2		1		
3													
4		7	8		9		10		11		12		
5													
6		18	17		16		15		14		13		
7													
8		19	20		21		22		23		24		
9													
10		30	29		28		27		26		25		
11													
12		31	32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

C-3 Section Corner common to sec's 5,6,7,8, T21N,R3E

C-4 Quarter Corner common to sec's 7&8, T21N,R3E

1846 - GLO - B.F.Hall - Set post corner Sections 5,6,7,8.  
Spruce Pine 6" S88 1/2°W 4.51 chains  
Spruce Pine 8" N87 1/2°W 4.64 chains  
1974 - Cert. of Survey - L.2, p.15 - Norman C. Caldwell, P.S.#12018 - Shows corner on survey. Shows distances to South and East.  
1974 - Corner References - L.2, p.16 - Norman C. Caldwell, P.S.#12018 - Fd. 3/4" Pipe, set spike in center w/RLS cap.  
S45°E 46.62' 1/2" Bar and corner post.  
N20°W 44.7' 20" R. Oak  
N17°E 38.6' 18" R. Oak  
1974 - L.C.R.C. - L.1, p.66 - Norman C. Caldwell, P.S.#12018 - Same info as L.2, p.16.

1846 - GLO - B.F.Hall - Set quarter sec. post.  
Y. Pine 20" S26°W 25 links  
Spruce Pine 10" S70°E 22 links  
1974 - Cert. of Survey - L.2, p.15 - Norman C. Caldwell, P.S.#12018 - Set corner by single proportion between C3 and C5.  
1974 - Corner References - L.2, p.16 - Norman C. Caldwell, P.S.#12018 - Set 1/2" bar & RLS cap. Placed DNR post alongside.  
S84°W 8.9' 12" J.Pine  
N89°E 19.62' 12" J.Pine  
S13°E 26.65' 10" J.Pine  
1974 - L.C.R.C. - L.1, p.66 - Norman C. Caldwell, P.S.#12018 - Same info as L.2, p.16.

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

C-3 Section Corner common to sec's 5,6,7,8, T21N,R3E

C-4 Quarter Corner common to sec's 7&8, T21N,R3E

Fd. 1/2"x18" rebar 14" below grade in gravel road & 2-track intersection fitting N. Caldwell's survey in section 8.  
Corner is 2' East of C/L 2-track to South, in line with gravel road to north and 9' South of E-W C/L trail road. Fd. no other evidence to dispute the location for the corner. Accepted fd. 1/2"x18" rebar as the best available evidence for the position of the original corner. Replaced fd. 1/2"x18" rebar with a stamped 4" dia. DNR alum. cap on 1"x36" galvanized pipe 6" below grade.

Fd. 1/2"x18" CIR#12018 alongside cedar guard post, per L.C.R.C., L.1, p.66 - Corner is 20' East of C/L N-S 2-track and 18' South of trail going East. Fd. no other evidence to dispute the location for the corner. Accepted fd. 1/2"x18" CIR rebar as a careful and faithful reestablishment of the position of the original corner. Replaced fd. 1/2"x18" CIR with a stamped 4" dia. DNR alum. cap on 1"x36" galvanized pipe at grade.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

C-3 Section Corner common to sec's 5,6,7,8, T21N,R3E

C-4 Quarter Corner common to sec's 7&8, T21N,R3E

Set stamped 4" Dia. Alum. DNR cap on 1"x36" galv. Pipe

Set stamped 4" Dia. Alum. DNR cap on 1"x36" galv. Pipe

Wit: N56°E 65.98' to set N&T on NW side 3" J.Pine  
S47°E 20.93' to fd. nail on SW side P.Pole  
S76°W 56.43' to set N&T on N side 22" Oak  
N59°W 66.16' to set N&T on NE side 7" W.Oak ('XBT')  
S45°E 46.7' to fd. 1/2" Bar

Wit: N36°E 13.95' to set N&T at old N&T on W side 14" J.Pine  
N82°E 18.92' to set N&T on S side 5" J.Pine ('XBT')  
N05°W 39.40' to set N&T on E side 5" Oak ('XBT')  
S84°W 8.84' to fd. nail in bot. blaze of dead 12" J.Pine  
N45°W 44.78' to set N&T at old N&T on NE side 13" Oak  
S42°E 1.25' to NW face of old cedar guard post w/ loc. Tag.  
Set Blue Carsonite post 1' North.

Signed by:

Carl T. Kiiskila

Surveyor's Michigan License No.: 33981

Date:

8-13-09

