

# LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:  
Ogemaw  
(County)

Located In

Corner Code #

1. Public Land Survey T 21N R 3E B-2  
T R  
2. Property Controlling in Section S 6 T 21N R 3E 8  
S T R  
3. Miscellaneous Property in Section S T R  
S T R

4. Lot No: Recorded Plat:

5. Private Claims:

I, Carl T. Kiiskila, in a field survey on January 31, 2006 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

**NOTE:** Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

B-2 Sept. 1970 Norman Parker R.L.S. #16939 set a 1/2" x 18" bar at the intersection of the one - quarter lines.

Wit: 7" J. Pine S51°W 18.5'  
5" J. Pine S73°E 12.0'

8- This corner position was not established during the original government survey.

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

B-2 Found a 1/2" bar as set by N. Parker and accepted by local surveyors for the center of section 6.

8- Established the Northwest corner of the Northeast quarter of the Southwest quarter of section 6 as per B.L.M. instructions for the subdivision of a section.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

B-2 Found 1/2" bar added P.S. cap #33981

Wit: 7" J. Pine S87°W 13.25'  
9" Oak N22°W 16.72'  
10" J. Pine S47°E 42.63'  
9" J. Pine S30°W 21.33'  
Centerline of Gravel Road North 46'±

8- Set 5/8" X 32" rered with P.S. cap #33981

Wit: 12" Oak S24°W 24.23'  
14" R. Pine N86°W 35.93'  
NE Cor. Garage S10°E 60.57'  
P. Pole N43°E 98.93'  
Centerline of Gravel Road North 53'±

Signed by:

Carl T. Kiiskila

Date:

2/13/06

Surveyor's Michigan License No.:

33981

