

# SURVEY & REMONUMENTATION

MAR 02 2001

## LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

SECTION

For corners in

ONTONAGON  
(County)

Located in:

Corner Code #

1. Public Land Survey

T48N R41W

M - 1

T49N R41W

M - 13

T48N R40W

A - 1

T49N R40W

A - 13

2. Property Controlling  
in Section

S T R

S T R

3. Miscellaneous  
Property in Sec.

S T R

S T R

JUDITH D. ROEHM

1P

Ontonagon County

Page 1 of 1

LC 5/347

JEM Date 12/07/2000

Time 14:40:34

RECORDING FEE:

9.00

Register of Deeds Stamp & File Number

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_

5. Private Claims \_\_\_\_\_

Township corner Sections 1, 6, 31 & 36, T48N, T49N, R40W, R41W.

I, Earl W. Applekamp, in a field survey on Nov. 09, 2000, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

Original corner established by William A. Burt, U.S. Deputy Surveyor, summer of 1847. Set Cedar Post.

ORIGINAL BEARING TREES:

16" Maple S59°E 13 Links ( 8.58 Feet)  
14" Hemlock N79°W 31 Links (20.46 Feet)

PEER GROUP APPROVED  
Earl W. Applekamp  
COUNTY REGISTERED  
11-29-00

This corner was established 1.73 chains North of temporary corner set previously.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

No original evidence remains. The calculated position has a graded dirt road running North and South. Considerable farming activity has taken place in the area. Corner was re-established using the "leave swamp" call from the GLO notes on the East side of Section one, T48N R41W and adding the 1.73 chains North called for in T48N R40W GLO notes for the latitude. The center-line of the dirt road was used for the departure. This location is in conformance with calls to the corner East & West.

Research on file with the Ontonagon County Remonumentation Program Representative.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

At the corner position I set a 2½"X30" split base aluminum pipe with a 3" cap flush with the surface of the abandoned dirt road. Cap is stamped to read: County Remonumentation, T48N, T49N, R40W, R41W, S1, S6, S31, S36, 2000, P.S. 17610. I established four bearing objects.

Nail in P. Pole S04°E 172.92' - Nail in 6" Aspen S74°E 81.61'  
Nail in P. Pole N06°E 204.42' - 6' Steel Sign Post, North 0.59'



Signed by Earl W. Applekamp  
Surveyor's Michigan License No. 17610

Date November 24, 2000